



SPECS

FRAME	
SIZES	27.5: XS,S, 29: S,M,L,XL,XXL
COLORS	Mars Dust/Black/Chrome, Ultra Navy/Chrome
FRAME	ALUXX-grade aluminum, disc
FORK	SXC32-2 RCL, air spring, thru axle, steel steerer, 15x110 XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIPS	Giant Sole-O
STEM	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SEATPOST	Giant Contact Switch Core, 30.9 XS: 100x350mm (27.5) S: 100x350mm (27.5) / 100x350mm (29) M: 120x400mm (29) L: 120x400mm (29) XL: 120x400mm (29) XXL: 120x400mm (29)
SADDLE	Giant ErgoContact Trail
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	Shimano Deore M6100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore M6100, clutch
BRAKES	Shimano BR-MT200, hydraulic, Shimano RT-10 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano BL-MT200
CASSETTE	Shimano Deore M6100, 10x51
CHAIN	KMC X12
CRANKSET	ProWheel MPX, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
BOTTOM BRACKET	cartridge

WHEELS	
RIMS	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
HUBS	[F] Shimano, sealed bearing, 15x110 thru axle, [R] 12x142 thru-axle
SPOKES	stainless, 14g
TIRES	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
EXTRAS	2.4" max tire size

Price: ₹ 1,169.00

GEOMETRY

FRAME	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Seat Tube Length (mm)	380	420	450	480	500
Seat Post Insertion Depth (mm)	340	200	237	292	322
Seat Tube Angle	74.5°	74.5°	74.5°	74.5°	74.5°
Top Tube Length (mm)	581	604	629	653	676
Head Tube Length (mm)	95	105	125	140	155
Head Tube Angle	67.5°	67.5°	67.5°	67.5°	67.5°
Fork Rake (mm)	44	44	44	44	44
Trail (mm)	108.9	108.9	108.9	108.9	108.9
Wheelbase (mm)	1139	1164	1191	1217	1242
Chain Stay Length (mm)	455	455	455	455	455
Bottom Bracket Drop (mm)	55	55	55	55	55
Stack (mm)	597	606	625	639	653
Reach (mm)	415	436	456	476	495
Stand Over Height (mm)	715	709	709	710	707
Handlebar Width (mm)	690	690	690	690	690
Stem Length (mm)	50	60	70	80	90
Crank Length (mm)	170	170	170	175	175
Wheel Size	29"	29"	29"	29"	29"

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.