

TALON 0



ESPECIFICACIONES

CUADRO	
TALLAS	27.5: XS, S, 29: S, M, L, XL, XXL
COLORES	Stealth Chrome, Plasma Coral
CUADRO	ALUXX-grade aluminum, disc
HORQUILLA	SXC32-2 RCL, air spring, thru axle, steel steerer, 15x110 XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
COMPONENTES	
MANILLAR	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
PUÑOS	Giant Sole-O
POTENCIA	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
TIJA DE SILLÍN	Contact Switch AT Core, 30.9, dropper, remote under bar, 110-140mm travel XS: 395mm (27.5) S: 395mm (27.5/29) M: 395mm (29) L: 395mm (29) XL: 395mm (29) XXL: 395mm (29)
SILLÍN	Giant ErgoContact Trail
PEDALES	MTB caged
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore M6200, 1x12
CAMBIO TRASERO	Shimano Deore M7200, Shadow ES
FRENOS	Shimano BR-MT200, hydraulic, Shimano RT-10 rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	Shimano BL-MT201
CASETTE	Shimano Deore M6200, 10x51
CADENA	KMC X-12
JGO. PLATOS Y BIELAS	ProWheel MPX, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
CAJA DE PEDALIER	Cartridge

RUEDAS	
LLANTAS	Giant tubeless compatible 29 or 27.5, alloy, double wall, 21mm inner width
BUJES	[F] Shimano, sealed bearing, 15x110 thru axle, [R] 12x142 thru-axle
RADIOS	stainless, 14g
CUBIERTAS	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	2.4"
MÁXIMO TAMAÑO DE PLATO	32T

Precio: 1.099,00 €

GEOMETRÍA

CUADRO	S (29")	M (29")	L (29")	XL (29")
Longitud del tubo del sillín (mm)	380	420	450	480
Seat Post Insertion Depth (mm)	245	200	250	300
Ángulo del tubo del sillín	74,5°	74,5°	74,5°	74,5°
Longitud del tubo superior (mm) (mm)	581	604	629	653
Longitud del tubo de dirección (mm) (mm)	95	105	125	140
Ángulo del tubo de dirección	67,5°	67,5°	67,5°	67,5°
Inclinación de la horquilla (mm)	44	44	44	44
Trail (mm) (mm)	109	109	109	109
Distancia entre ejes (mm) (mm)	1140	1164	1191	1216
Longitud de la vaina (mm) (mm)	455	455	455	455
Caída del eje de pedalier (mm) (mm)	55	55	55	55
Stack (mm) (mm)	597	606	625	638
Reach (mm) (mm)	415	435	455	475
Altura del suelo al tubo (mm) (mm)	715	708	708	710
Ancho del manillar (mm) (mm)	760	760	760	760
Longitud de la potencia (mm) (mm)	40	50	60	60
Longitud de las bielas (mm) (mm)	170	170	170	175

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.