



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	27.5: XS,S,M,L, 29: S,M,L,XL,XXL
COLORIS	Blue Ashes
CADRE	ALUXX-Grade Aluminum, disc
FOURCHE	SXC32-2 RL 29, air spring, QR, alloy steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M: 100mm travel (27.5) / 100mm travel (29) L: 100mm travel (27.5) / 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Connect Trail, 31.8mm XS: 730mm (27.5) S: 780mm (27.5) / 780mm (29) M: 780mm (27.5) / 780mm travel (29) L: 780mm (27.5) / 780mm (29) XL: 780mm (29) XXL: 780mm (29)
POIGNÉES	Giant Sole-O
POTENCE	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (27.5) / 60mm travel (29) L: 70mm (27.5) / 70mm (29) XL: 80mm (29) XXL: 90mm (29)
TIGE DE SELLE	Giant Sport, 30.9 XS: 300mm (27.5) S: 300mm (27.5) / 375mm (29) M: 375mm (27.5) / 375mm travel (29) L: 375mm (27.5) / 375mm (29) XL: 375mm (29) XXL: 375mm (29)
SELLE	Giant custom
PÉDALES	MTB caged
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano Deore M6100, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano Deore M6100
FREINS	Shimano Deore BR-MT200, hydraulic, Shimano RT-10 rotors [F]180mm, [R]160mm
LEVIER DE FREIN	Shimano Deore BL-MT200
CASSETTE	Shimano Deore M6100, 10x51
CHAÎNE	KMC X12
PÉDALIER	ProWheel MPX, 30t (27.5) or 32t (29) XS: 165mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (27.5) / 175mm travel (29) L: 175mm (27.5) / 175mm (29) XL: 175mm (29) XXL: 175mm (29)
PÉDALIER	cartridge

ROUES	
JANTES	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
MOYEUX	Shimano, sealed bearing
RAYONS	stainless, 14g
PNEUS	Kenda Booster 27.5 or 29x2.4", wire bead
EXTRAS	2.4" max tire size, 32t max chainring size

GÉOMÉTRIE

CADRE	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (27.5")	L (29")	XL (29")	XXL (29")
Longueur de tube de selle (mm)	350	385	390	430	440	490	490	535	565
Angle de tube de selle	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°
Longueur du tube supérieur (mm)	544	569	577	597	599	618	620	639	658
Longueur du tube de direction (mm)	95	115	95	130	105	155	125	140	155
Angle du tube de direction	67,5°	67,5°	68,5°	67,5°	68,5°	67,5°	68,5°	68,5°	68,5°
Déport de fourche (mm)	42	42	51	42	51	42	51	51	51
Chasse (mm)	103	103	94	103	94	103	94	94	94
Empattement (mm)	1079	1106	1126	1137	1150	1162	1172	1192	1213
Longueur des bases (mm)	440	440	455	440	455	440	455	455	455
Hauteur du boîtier de pédalier (mm)	45	45	55	45	55	45	55	55	55
Stack (mm)	533	571	602	598	611	621	630	644	658
Reach (mm)	385	405	404	425	424	440	439	454	469
Hauteur d'enjambement (mm)	686	711	732	748	766	794	805	839	856
Largeur de cintre (mm)	780	780	780	780	780	780	780	780	780
Longueur de potence (mm)	40	50	50	60	60	70	70	80	90
Longueur des manivelles (mm)	165	170	170	175	175	175	175	175	175
Diamètre des roues	27.5"	27.5"	29"	27.5"	29"	27.5"	29"	29"	29"

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.