



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	27.5: XS,S, 29: S,M,L,XXL
COLORIS	Mars Dust/Black/Chrome, Ultra Navy/Chrome
CADRE	ALUXX-grade aluminum, disc
FOURCHE	SXC32-2 RCL, air spring, thru axle, steel steerer, 15x110 XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
POIGNÉES	Giant Sole-O
POTENCE	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
TIGE DE SELLE	Giant Contact Switch Core, 30.9 XS: 100x350mm (27.5) S: 100x350mm (27.5) / 100x350mm (29) M: 120x400mm (29) L: 120x400mm (29) XL: 120x400mm (29) XXL: 120x400mm (29)
SELLE	Giant ErgoContact Trail
PÉDALES	MTB caged
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano Deore M6100, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano Deore M6100, clutch
FREINS	Shimano BR-MT200, hydraulic, Shimano RT-10 rotors [F]180mm, [R]160mm
LEVIERS DE FREIN	Shimano BL-MT200
CASSETTE	Shimano Deore M6100, 10x51
CHAÎNE	KMC X12
PÉDALIER	ProWheel MPX, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
PÉDALIER	cartridge

ROUES	
JANTES	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
MOYEURS	[F] Shimano, sealed bearing, 15x110 thru axle, [R] 12x142 thru-axle
RAYONS	stainless, 14g
PNEUS	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
EXTRAS	2.4" max tire size

GÉOMÉTRIE

CADRE	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Longueur de tube de selle (mm)	345	375	380	420	450	480	500
Seat Post Insertion Depth (mm)	306	337	340	200	237	292	322
Angle de tube de selle	74,0°	74,0°	74,5°	74,5°	74,5°	74,5°	74,5°
Longueur du tube supérieur (mm)	542	562	581	604	629	653	676
Longueur du tube de direction (mm)	90	90	95	105	125	140	155
Angle du tube de direction	67,0°	67,0°	67,5°	67,5°	67,5°	67,5°	67,5°
Déport de fourche (mm)	44	44	44	44	44	44	44
Chasse (mm)	105,2	105,2	108,9	108,9	108,9	108,9	108,9
Empattement (mm)	1084	1104	1139	1164	1191	1217	1242
Longueur des bases (mm)	440	440	455	455	455	455	455
Hauteur du boîtier de pédalier (mm)	45	45	55	55	55	55	55
Stack (mm)	548	548	597	606	625	639	653
Reach (mm)	385	405	415	436	456	476	495
Hauteur d'enjambement (mm)	684	684	715	709	709	710	707
Largeur de cintre (mm)	690	690	690	690	690	690	690
Longueur de potence (mm)	40	50	50	60	70	80	90
Longueur des manivelles (mm)	170	165	170	170	170	175	175
Diamètre des roues	27.5"	27.5"	29"	29"	29"	29"	29"

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.