

TALON 0



TECHNIQUES

CADRE	
TAILLES	27.5: XS, S, 29: S, M, L, XL, XXL
COLORIS	Stealth Chrome, Plasma Coral
CADRE	ALUXX-grade aluminum, disc
FOURCHE	SXC32-2 RCL, air spring, thru axle, tapered steerer, 15x110 XS: 80mm (27.5) S: 80mm (27.5) / 100mm (29) M: 100mm (29) L: 100mm (29) XL: 100mm (29) XXL: 100mm (29)
COMPOSANTS	
CINTRE	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
POIGNÉES	Giant Sole-O
POTENCE	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
TIGE DE SELLE	Contact Switch AT Core, 30.9, dropper, remote under bar, 110-140mm travel XS: 395mm (27.5) S: 395mm (27.5/29) M: 395mm (29) L: 395mm (29) XL: 395mm (29) XXL: 395mm (29)
SELLE	Giant ErgoContact Trail
PÉDALES	MTB caged, 9/16" (nylon body, steel cage)
DÉRAILLEUR	
MANETTES	Shimano Deore 1x12, SL-M6200-R / SL-M6100-R
DÉRAILLEUR ARRIÈRE	Shimano Deore, RD-M6100-SGS / RD-M7200, Shadow ES
FREINS	Shimano BR-MT200, hydraulic, RT10 centerlock rotors [F] 180mm, [R] 160mm
LEVIER DE FREIN	Shimano BL-MT201
CASSETTE	Shimano Deore, CS-M6100-12 / CS-M6200-12, 10-51, 12-speed
CHAÎNE	KMC X-12
PÉDALIER	ProWheel MPX-CR0945-TT, steel C.Ring, w/ O Chain Guard, 52.5mm chainline XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
BOITIER DE PÉDALIER	Cartridge

ROUES	
JANTES	Giant GX03V 29/27.5, Tubeless Compatible, 6061 aluminum, double wall, 21mm inner width, disc, 28h
MOYEUX	[F] Giant Tracker Hub, HB-TC500-15-B / M9202-F, centerlock mount, 6-bolt rotor mount, [R] Giant Tracker Hub, FH-TC500-MS / M9201-R, microspine body, HG type. 15x110 TA F / 12x142 TA R
RAYONS	Stainless 14G, black
PNEUS	Maxxis Rekon Race 29x2.2 / Maxxis Rekon 27.5x2.4, 60 TPI, wire bead
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
DÉGAGEMENT MAX DES PNEUS	2.4"
TAILLE MAXIMALE DU PLATEAU	32T

Prix Public Conseillé: 1 150,00 €

GÉOMÉTRIE

CADRE	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Longueur de tube de selle (mm)	380	420	450	480	500
Seat Post Insertion Depth (mm)	245	200	250	300	330
Angle de tube de selle	74,5°	74,5°	74,5°	74,5°	74,5°
Longueur du tube supérieur (mm)	581	604	629	653	676
Longueur du tube de direction (mm)	95	105	125	140	155
Angle du tube de direction	67,5°	67,5°	67,5°	67,5°	67,5°
Déport de fourche (mm)	44	44	44	44	44
Trail (mm)	109	109	109	109	109
Empattement (mm)	1140	1164	1191	1216	1242
Longueur des bases (mm)	455	455	455	455	455
Drop du boîtier de pédalier (mm)	55	55	55	55	55
Stack (mm)	597	606	625	638	652
Reach (mm)	415	435	455	475	495
Hauteur en statique (mm)	715	708	708	710	707
Largeur de cintre (mm)	760	760	760	760	760
Longueur de potence (mm)	40	50	60	60	80
Longueur des manivelles (mm)	170	170	170	175	175

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).