

TALON 0



SPECIFIKACIJE

OKVIR	
VELIKOSTI	27.5: XS, S, 29: S, M, L, XL, XXL
BARVE	Stealth Chrome, Plasma Coral
OKVIR	ALUXX-grade aluminum, disc
VILICE	SXC32-2 RCL, air spring, thru axle, steel steerer, 15x110 XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
KOMPONENTE	
KRMILO	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIPS	Giant Sole-O
OPORA KRMILA	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
OPORA SEDEŽA	Contact Switch AT Core, 30.9, dropper, remote under bar, 110-140mm travel XS: 395mm (27.5) S: 395mm (27.5/29) M: 395mm (29) L: 395mm (29) XL: 395mm (29) XXL: 395mm (29)
SEDEŽ	Giant ErgoContact Trail
PEDALA	MTB caged
POGON	
PRESTAVNE ROČICE	Shimano Deore M6200, 1x12
ZADNJI MENJALNIK	Shimano Deore M7200, Shadow ES
ZAVORE	Shimano BR-MT200, hydraulic, Shimano RT-10 rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Shimano BL-MT201
VERIŽNIK	Shimano Deore M6200, 10x51
VERIGA	KMC X-12
GONILKE Z VERIŽNIKI	ProWheel MPX, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
BOTTOM BRACKET	Cartridge

OBROČNIKI	
OBROČI	Giant tubeless compatible 29 or 27.5, alloy, double wall, 21mm inner width
PESTA	[F] Shimano, sealed bearing, 15x110 thru axle, [R] 12x142 thru-axle
NAPERE	stainless, 14g
PLAŠČI	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
LIMITS	
MAX TIRE CLEARANCE	2.4"
MAX CHAINRING SIZE	32T

GEOMETRIJA

OKVIR	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Dolžina sedežne cevi (mm)	345	375	380	420	450	480	500
Seat Post Insertion Depth (mm)	300	340	245	200	250	300	330
Kot sedežne cevi	74,0°	74,0°	74,5°	74,5°	74,5°	74,5°	74,5°
Top Tube Length (mm)	542	562	581	604	629	653	676
Višina glave okvirja (mm)	90	90	95	105	125	140	155
Krmilni kot	67,0°	67,0°	67,5°	67,5°	67,5°	67,5°	67,5°
Zamik vpetja osi (mm)	44	44	44	44	44	44	44
Trail (mm)	105	105	109	109	109	109	109
Medosna razdalja (mm)	1084	1104	1140	1164	1191	1216	1242
Dolžina cevi ob verigi (mm)	440	440	455	455	455	455	455
Bottom Bracket Drop (mm)	45	45	55	55	55	55	55
Oddaljenost zgornje cevi od gonilne osi (mm)	548	548	597	606	625	638	652
Doseg (mm)	385	405	415	435	455	475	495
Višina zgornje cevi (mm)	684	684	715	708	708	710	707
Širina krmila (mm)	760	760	760	760	760	760	760
Dolžina opore krmila (mm)	40	50	40	50	60	60	80
Dolžina gonilke (mm)	165	165	170	170	170	175	175

Vse navedene specifikacije se lahko spremenijo brez obvestila.