

TALON 0



SPECS

RAM	
STORLEKAR	27.5: XS,S,M,L, 29: S,M,L,XL,XXL
FÄRGER	Blue Ashes
RAM	ALUXX-Grade Aluminum, disc
GAFFEL	SXC32-2 RL 29, air spring, QR, alloy steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M: 100mm travel (27.5) / 100mm travel (29) L: 100mm travel (27.5) / 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
BAKDÄMPARE	N/A
KOMPONENTER	
STYRE	Giant Connect Trail, 31.8mm XS: 730mm (27.5) S: 780mm (27.5) / 780mm (29) M: 780mm (27.5) / 780mm travel (29) L: 780mm (27.5) / 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GREPPAR	Giant Sole-O
STAM	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (27.5) / 60mm travel (29) L: 70mm (27.5) / 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SADELSTOLPE	Giant Sport, 30.9 XS: 300mm (27.5) S: 300mm (27.5) / 375mm (29) M: 375mm (27.5) / 375mm travel (29) L: 375mm (27.5) / 375mm (29) XL: 375mm (29) XXL: 375mm (29)
SADEL	Giant custom
PEDALER	MTB caged
DRIVLINA	
VÄXLAR	Shimano Deore M6100, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	Shimano Deore M6100
BROMSAR	Shimano Deore BR-MT200, hydraulic, Shimano RT-10 rotors [F]180mm, [R]160mm
BROMSSPAKAR	Shimano Deore BL-MT200
KASSETT	Shimano Deore M6100, 10x51
KEDJA	KMC X12
VEVPARTI	ProWheel MPX, 30t (27.5) or 32t (29) XS: 165mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (27.5) / 175mm travel (29) L: 175mm (27.5) / 175mm (29) XL: 175mm (29) XXL: 175mm (29)
BROMSREGLAGE	cartridge

HJUL	
FÄLGAR	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NAV	Shimano, sealed bearing
EKRAR	stainless, 14g
DÄCK	Kenda Booster 27.5 or 29x2.4", wire bead
EXTRAFUNKTIONER	2.4" max tire size, 32t max chainring size

Price: 12 390,00 kr

GEOMETRY

RAM	M (29")
Längd sadelrör (mm)	440
Vinkel sadelrör	74,0°
Topprörets längd (mm)	599
Styrhuvud Längd (mm)	105
Vinkel styrhuvud	68,5°
Gaffelvinkel (mm)	51
Spår (mm)	94
Hjulbas (mm)	1150
Kedjestagslängd (mm)	455
Nedre fäste Drop (mm)	55
Stack (mm)	611
Reach (mm)	424
Stå över höjden (mm)	766
Styrets bredd (mm)	780
Stamlängd (mm)	60
Vevlängd (mm)	175
Hjulstorlek	29"

All specifications listed are subject to change without notice.