



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	27.5: XS,S, 29: S,M,L,XXL
FARBE	Metallic Blue, Charcoal
RAHMEN	ALUXX-grade aluminum, disc
GABEL	SXC32-3 RL, coil spring, thru axle, steel steerer, 15x110 XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIFFE	Giant Sole-O
VORBAU	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SATTELSTÜTZE	Giant Contact Switch Core, 30.9 XS: 100x350mm (27.5) S: 100x350mm (27.5) / 100x350mm (29) M: 120x400mm (29) L: 120x400mm (29) XL: 120x400mm (29) XXL: 120x400mm (29)
SATTEL	Giant ErgoContact Trail
PEDALE	MTB caged
ANTRIEB	
SCHALTHEBEL	Shimano CUES SL-6000, 1x10
UMWERFER	N/A
SCHALTWERK	Shimano CUES RD-U6000, clutch
BREMSEN	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
BREMSEBEL	Tektro HDC M275
KASSETTE	Shimano CUES, CS-LG300, 11x48
KETTE	KMC X-11
KURBEL	ProWheel Charm, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
TRETLAGER	cartridge

LAUFRÄDER	
FELGEN	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NABE	[F] Giant Tracker hub, sealed bearing, 15x110 thru axle. [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
SPEICHEN	stainless, 14g
REIFEN	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
EXTRAS	2.4" max tire size

GEOMETRIEDATEN

RAHMEN	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Sitzrohrlänge (mm)	345	375	380	420	450	480	500
Seat Post Insertion Depth (mm)	306	337	340	200	237	292	322
Sitzrohrwinkel	74.0°	74.0°	74.5°	74.5°	74.5°	74.5°	74.5°
Oberrohrlänge (mm)	542	562	581	604	629	653	676
Steuerrohr-Länge (mm)	90	90	95	105	125	140	155
Steuerrohr-Winkel	67.0°	67.0°	67.5°	67.5°	67.5°	67.5°	67.5°
Gabelneigung (mm)	44	44	44	44	44	44	44
Trail (mm)	105.2	105.2	108.9	108.9	108.9	108.9	108.9
Radstand (mm)	1084	1104	1139	1164	1191	1217	1242
Kettenstreben-Länge (mm)	440	440	455	455	455	455	455
Tretlager-Höhe (mm)	45	45	55	55	55	55	55
Stack (mm)	548	548	597	606	625	639	653
Reach (mm)	385	405	415	436	456	476	495
Überstandshöhe (mm)	684	684	715	709	709	710	707
Lenkerbreite (mm)	690	690	690	690	690	690	690
Vorbaulänge (mm)	40	50	50	60	70	80	90
Kurbellänge (mm)	170	165	170	170	170	175	175
Radgrösse	27.5"	27.5"	29"	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.