

TALON 1



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L, XL, XXL
RAHMEN	ALUXX-Grade Butted Aluminum
GABEL	GIANT SXC32-2 RCL Alloy SingleAir 29"/27.5" 15x110 TA 80mm(27.5") Spring: Air 80mm(27.5")/100mm(29") Spring: Air M, L, XL, XXL: 100mm(29") Spring: Air
KOMPONENTEN	
LENKER	Giant Connect Trail, 780mm x 31.8mm, GA 690mm XS: 690mm(27.5") S: 690mm(27.5") /750mm(29") M, L, XL, XXL: 780mm(29")
GRIFFE	Giant Sole-O Grip
VORBAU	Giant Sport, 7 Degree XS: 40(27.5") S: 50(27.5"/29") M: 60(27.5"/29") L: 70(27.5"/29") XL: 80(29") XXL: 90(29")
SATTELSTÜTZE	Giant Sport, 30.9, SP217
SATTEL	Giant ErgoContact Trail
PEDALE	MTB caged
ANTRIEB	
SCHALTHEBEL	microSHIFT Advent, 1x11
SCHALTWERK	microSHIFT Advent, clutch
BREMSEN	Tektro HD M3121, hydraulic, Tektro rotors [F]180mm, [R]160mm
BREMSEBEL	Tektro HD M3121
KASSETTE	microSHIFT Advent MX, 11x50
KETTE	KMC X11
KURBEL	ProWheel Charm, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
TRETLAGER	cartridge

LAUFRÄDER	
FELGEN	Giant tubeless compatible 29 or 27.5, alloy, double wall, 21mm inner width
NABE	[F] Giant Tracker hub, sealed bearing, 15x110 thru axle. [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
SPEICHEN	Stainless 14G
REIFEN	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
LIMITS	
MAX TIRE CLEARANCE	maximum Rear tire size 2.4"
MAX CHAINRING SIZE	maximum chainring size 32T

GEOMETRIEDATEN

RAHMEN	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Sitzrohrlänge (mm)	345	375	380	420	450	480	500
Seat Post Insertion Depth (mm)	300	340	245	200	250	300	330
Sitzrohrwinkel	74.0°	74.0°	74.5°	74.5°	74.5°	74.5°	74.5°
Oberrohrlänge (mm)	542	562	581	604	629	653	676
Steuerrohr-Länge (mm)	90	90	95	105	125	140	155
Steuerrohr-Winkel	67.0°	67.0°	67.5°	67.5°	67.5°	67.5°	67.5°
Gabelneigung (mm)	44	44	44	44	44	44	44
Trail (mm)	105	105	109	109	109	109	109
Radstand (mm)	1084	1104	1140	1164	1191	1216	1242
Kettenstreben-Länge (mm)	440	440	455	455	455	455	455
Tretlager-Höhe (mm)	45	45	55	55	55	55	55
Stack (mm)	548	548	597	606	625	638	652
Reach (mm)	385	405	415	435	455	475	495
Überstandshöhe (mm)	684	684	715	708	708	710	707
Lenkerbreite (mm)	760	760	760	760	760	760	760
Vorbaulänge (mm)	40	50	40	50	60	60	80
Kurbellänge (mm)	165	165	170	170	170	175	175

Spezifikations-, Preis- und Farbänderungen vorbehalten.