

TALON 1



SPECS

FRAME	
SIZES	XS, S, M, L, XL, XXL
FRAME	ALUXX-Grade Butted Aluminum
FORK	GIANT SXC32-2 RCL Alloy SingleAir 29"/27.5" 15x110 TA 80mm(27.5") Spring: Air 80mm(27.5")/100mm(29") Spring: Air M, L, XL, XXL: 100mm(29") Spring: Air
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 780mm x 31.8mm, GA 690mm XS: 690mm(27.5") S: 690mm(27.5") /750mm(29") M, L, XL, XXL: 780mm(29")
GRIPS	Giant Sole-O Grip
STEM	Giant Sport, 7 Degree XS: 40(27.5") S: 50(27.5"/29") M: 60(27.5"/29") L: 70(27.5"/29") XL: 80(29") XXL: 90(29")
SEATPOST	Giant Sport, 30.9, SP217
SADDLE	Giant ErgoContact Trail
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	Microshift Advent MX 1x11 SL-M7115-R
REAR DERAILLEUR	Microshift Advent 1x11 RD-M7015M
BRAKES	Tektro HD M3121 [F] 180mm [R] 160mm, Hydraulic
BRAKE LEVERS	Tektro HD-M3121 M275
CASSETTE	Microshift Advent MX 1x11 CS-H114 11-50T
CHAIN	KMC X11
CRANKSET	Prowheel Charm w/Steel C.Ring, 32t Prowheel Charm w/Steel C.Ring, 30t w/O Chain Guard for 29" 52.5mm chainline
BOTTOM BRACKET	FP-B902W

WHEELS	
RIMS	Giant - Tubeless Compatible, 6061 Aluminum, Double Wall, 21mm Inner Width
HUBS	Giant [F] 15x110 thru axle, [R] 12x142 thru-axle
SPOKES	Stainless 14G
TIRES	Maxxis Rekon Race 29x2.4" Rekon 27.5x2.4" 60 TPI wire bead
LIMITS	
MAX TIRE CLEARANCE	maximum Rear tire size 2.4"
MAX CHAINRING SIZE	maximum chainring size 32T

Recommended Retail Price: \$1,000.00

GEOMETRY

FRAME	M (29")	L (29")	XL (29")
Seat Tube Length (inch)	16.5	17.7	18.9
Seat Post Insertion Depth (inch)	7.9	9.8	11.8
Seat Tube Angle	74.5°	74.5°	74.5°
Top Tube Length (inch)	23.8	24.8	25.7
Head Tube Length (inch)	4.1	4.9	5.5
Head Tube Angle	67.5°	67.5°	67.5°
Fork Rake (inch)	1.7	1.7	1.7
Trail (inch)	4.3	4.3	4.3
Wheelbase (inch)	45.8	46.9	47.9
Chain Stay Length (inch)	17.9	17.9	17.9
Bottom Bracket Drop (inch)	2.2	2.2	2.2
Stack (inch)	23.9	24.6	25.1
Reach (inch)	17.1	17.9	18.7
Stand Over Height (inch)	27.9	27.9	28
Handlebar Width (inch)	29.9	29.9	29.9
Stem Length (inch)	2	2.4	2.4
Crank Length (inch)	6.7	6.7	6.9

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*