

TALON 1



ESPECIFICACIONES

CUADRO	
TALLAS	27.5: XS,S, 29: S,M,L,XL,XXL
COLORES	Charcoal
CUADRO	ALUXX-grade aluminum, disc
HORQUILLA	SXC32-3 RL, coil spring, thru axle, steel steerer, 15x110 XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
AMORTIGUADOR	N/A
COMPONENTES	
MANILLAR	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
PUÑOS	Giant Sole-O
POTENCIA	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
TIJA DE SILLÍN	Giant Contact Switch Core, 30.9 XS: 100x350mm (27.5) S: 100x350mm (27.5) / 100x350mm (29) M: 120x400mm (29) L: 120x400mm (29) XL: 120x400mm (29) XXL: 120x400mm (29)
SILLÍN	Giant ErgoContact Trail
PEDALES	MTB caged
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano CUES SL-6000, 1x10
DESVIADOR	N/A
CAMBIO TRASERO	Shimano CUES RD-U6000, clutch
FRENOS	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	Tektro HDC M275
CASETTE	Shimano CUES, CS-LG300, 11x48
CADENA	KMC X-11
JGO. PLATOS Y BIELAS	ProWheel Charm, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
CAJA DE PEDALIER	cartridge

RUEDAS	
LLANTAS	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
BUJES	[F] Giant Tracker hub, sealed bearing, 15x110 thru axle. [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
RADIOS	stainless, 14g
CUBIERTAS	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
EXTRAS	2.4" max tire size

Precio: 899,00 €

GEOMETRÍA

CUADRO	XS (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Longitud del tubo del sillín (mm)	345	380	420	450	480	500
Seat Post Insertion Depth (mm)	306	340	200	237	292	322
Ángulo del tubo del sillín	74,0°	74,5°	74,5°	74,5°	74,5°	74,5°
Longitud del tubo superior (mm) (mm)	542	581	604	629	653	676
Longitud del tubo de dirección (mm) (mm)	90	95	105	125	140	155
Ángulo del tubo de dirección	67,0°	67,5°	67,5°	67,5°	67,5°	67,5°
Inclinación de la horquilla (mm)	44	44	44	44	44	44
Trail (mm) (mm)	105,2	108,9	108,9	108,9	108,9	108,9
Distancia entre ejes (mm) (mm)	1084	1139	1164	1191	1217	1242
Longitud de la vaina (mm) (mm)	440	455	455	455	455	455
Caída del eje de pedalier (mm) (mm)	45	55	55	55	55	55
Stack (mm) (mm)	548	597	606	625	639	653
Reach (mm) (mm)	385	415	436	456	476	495
Altura del suelo al tubo (mm) (mm)	684	715	709	709	710	707
Ancho del manillar (mm) (mm)	690	690	690	690	690	690
Longitud de la potencia (mm) (mm)	40	50	60	70	80	90
Longitud de las bielas (mm) (mm)	170	170	170	170	175	175
Tamaño de ruedas	27.5"	29"	29"	29"	29"	29"

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.