

TALON 1

GIANT



TECHNIQUES

CADRE	
TAILLES	27.5: XS,S, 29: S,M,L,XXL
COLORIS	Metallic Blue, Charcoal
CADRE	ALUXX-grade aluminum, disc
FOURCHE	SXC32-3 RL, coil spring, thru axle, steel steerer, 15x110 XS/S: 80mm travel (27.5) S/M/L/XXL: 100mm travel (29)
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Connect Trail, 31.8mm XS/S: 690mm (27.5) S: 750mm (29) M/L/XXL: 780mm (29)
POIGNÉES	Giant Sole-O
POTENCE	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5-29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
TIGE DE SELLE	Giant Contact Switch Core, 30.9 XS/S: 100x350mm (27.5-29) M/L/XXL: 120x400mm (29)
SELLE	Giant ErgoContact Trail
PÉDALES	MTB caged
DÉRAILLEUR	
MANETTES	Shimano CUES SL-6000, 1x10
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano CUES RD-U6000, clutch
FREINS	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
LEVIERS DE FREIN	Tektro HDC M275
CASSETTE	Shimano CUES, CS-LG300, 11x48
CHAÎNE	KMC X-11
PÉDALIER	ProWheel Charm, 32t (27.5) or 30t (29) XS/S: 165mm (27.5) S/M/L: 170mm (29) XL/XXL: 175mm (29)
BOITIER DE PÉDALIER	cartridge

ROUES	
JANTES	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
MOYEURS	[F] Giant Tracker hub, sealed bearing, 15x110 thru axle. [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
RAYONS	stainless, 14g
PNEUS	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
EXTRAS	2.4" max tire size
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 900,00 €

GÉOMÉTRIE

CADRE	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Longueur de tube de selle (mm)	345	375	380	420	450	480	500
Seat Post Insertion Depth (mm)	306	337	340	200	237	292	322
Angle de tube de selle	74,0°	74,0°	74,5°	74,5°	74,5°	74,5°	74,5°
Longueur du tube supérieur (mm)	542	562	581	604	629	653	676
Longueur du tube de direction (mm)	90	90	95	105	125	140	155
Angle du tube de direction	67,0°	67,0°	67,5°	67,5°	67,5°	67,5°	67,5°
Déport de fourche (mm)	44	44	44	44	44	44	44
Trail (mm)	105,2	105,2	108,9	108,9	108,9	108,9	108,9
Empattement (mm)	1084	1104	1139	1164	1191	1217	1242
Longueur des bases (mm)	440	440	455	455	455	455	455
Drop du boîtier de pédalier (mm)	45	45	55	55	55	55	55
Stack (mm)	548	548	597	606	625	639	653
Reach (mm)	385	405	415	436	456	476	495
Hauteur en statique (mm)	684	684	715	709	709	710	707
Largeur de cintre (mm)	690	690	690	690	690	690	690
Longueur de potence (mm)	40	50	50	60	70	80	90
Longueur des manivelles (mm)	170	165	170	170	170	175	175
Diamètre des roues	27.5"	27.5"	29"	29"	29"	29"	29"

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.