

TALON 1



SPECS

QUADRO	
TAMANHOS	27.5: XS,S, 29: S,M,L,XL,XXL
CORES	Metallic Blue, Charcoal
QUADRO	ALUXX-grade aluminum, disc
FORQUILHA	SXC32-3 RL, coil spring, thru axle, steel steerer, 15x110 XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
AMORTECEDORES	N/A
COMPONENTES	
GUIADOR	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
PUNHOS	Giant Sole-O
AVANÇO	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
ESPIGÃO DE SELIM	Giant Contact Switch Core, 30.9 XS: 100x350mm (27.5) S: 100x350mm (27.5) / 100x350mm (29) M: 120x400mm (29) L: 120x400mm (29) XL: 120x400mm (29) XXL: 120x400mm (29)
SELIM	Giant ErgoContact Trail
PEDAIS	MTB caged
TRANSMISSÃO	
MANETES	Shimano CUES SL-6000, 1x10
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	Shimano CUES RD-U6000, clutch
TRAVÕES	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
MANÍPULOS DOS TRAVÕES	Tektro HDC M275
CASSETTE	Shimano CUES, CS-LG300, 11x48
CORRENTE	KMC X-11
CONJUNTO PEDALEIRO	ProWheel Charm, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
MOVIMENTO CENTRAL	cartridge

RODAS	
AROS	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
CUBOS	[F] Giant Tracker hub, sealed bearing, 15x110 thru axle. [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
RAIOS	stainless, 14g
PNEUS	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
EXTRAS	2.4" max tire size

Preço: 799,00 €

GEOMETRIA

QUADRO	XS (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Comprimento do tubo do assento (mm)	345	380	420	450	480	500
Seat Post Insertion Depth (mm)	306	340	200	237	292	322
Ângulo do tubo do assento	74,0°	74,5°	74,5°	74,5°	74,5°	74,5°
Comprimento do tubo superior (mm)	542	581	604	629	653	676
Comprimento do tubo principal (mm)	90	95	105	125	140	155
Ângulo do tubo principal	67,0°	67,5°	67,5°	67,5°	67,5°	67,5°
Garfo ancinho (mm)	44	44	44	44	44	44
Trilha (mm)	105,2	108,9	108,9	108,9	108,9	108,9
distância entre eixos (mm)	1084	1139	1164	1191	1217	1242
Comprimento Chain Stay (mm)	440	455	455	455	455	455
Suporte inferior (mm)	45	55	55	55	55	55
Pilha (mm)	548	597	606	625	639	653
Alcançar (mm)	385	415	436	456	476	495
Altura do standover (mm)	684	715	709	709	710	707
Largura do guidão (mm)	690	690	690	690	690	690
Comprimento da haste (mm)	40	50	60	70	80	90
Comprimento da Manivela (mm)	170	170	170	170	175	175
Tamanho da roda	27.5"	29"	29"	29"	29"	29"

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.