



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	27.5: XS,S, 29: S,M,L,XL,XXL
FARBY	Metallic Blue, Charcoal
RÁM	ALUXX-grade aluminum, disc
VIDLICA	SXC32-3 RL, coil spring, thru axle, steel steerer, 15x110 XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
TLMIČ	N/A
KOMPONENTY	
RIADIDLÁ	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIPY	Giant Sole-O
PREDSTAVEC	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SEDOVKA	Giant Contact Switch Core, 30.9 XS: 100x350mm (27.5) S: 100x350mm (27.5) / 100x350mm (29) M: 120x400mm (29) L: 120x400mm (29) XL: 120x400mm (29) XXL: 120x400mm (29)
SEDADLO	Giant ErgoContact Trail
PEDÁLE	MTB caged
POHON	
RADENIE	Shimano CUES SL-6000, 1x10
PREŠMYKAČ	N/A
PREHADZOVAČKA	Shimano CUES RD-U6000, clutch
BRZDY	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
BRZDOVÉ PÁKY	Tektro HDC M275
KAZETA	Shimano CUES, CS-LG300, 11x48
REŤAZ	KMC X-11
KLUKY	ProWheel Charm, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
STREDOVÉ ZLOŽENIE	cartridge

KOLESÁ	
RÁFIKY	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NÁBOJE	[F] Giant Tracker hub, sealed bearing, 15x110 thru axle. [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
ŠPICE	stainless, 14g
PNEUMATIKY	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
DOPLNKY	2.4" max tire size

Cena: 899 €

GEOMETRIA

RÁM	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Dĺžka sedlovej trubky (mm)	345	375	380	420	450	480	500
Hĺbka vloženia sedlovky (mm)	306	337	340	200	237	292	322
Uhol sedlovej trubky	74,0°	74,0°	74,5°	74,5°	74,5°	74,5°	74,5°
Dĺžka hornej rámovej trubky (mm)	542	562	581	604	629	653	676
Dĺžka hlavovej trubky (mm)	90	90	95	105	125	140	155
Uhol hlavovej trubky	67,0°	67,0°	67,5°	67,5°	67,5°	67,5°	67,5°
Offset vidlice (mm)	44	44	44	44	44	44	44
Trail (mm)	105,2	105,2	108,9	108,9	108,9	108,9	108,9
Rázvor (mm)	1084	1104	1139	1164	1191	1217	1242
Dĺžka zadnej stavby (mm)	440	440	455	455	455	455	455
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	45	45	55	55	55	55	55
Stack - výška riadenia (mm)	548	548	597	606	625	639	653
Reach (mm)	385	405	415	436	456	476	495
Výška rámu od zeme (mm)	684	684	715	709	709	710	707
Šírka riaditok (mm)	690	690	690	690	690	690	690
Dĺžka predstavca (mm)	40	50	50	60	70	80	90
Dĺžka klúku (mm)	170	165	170	170	170	175	175
Rozmer kolies	27.5"	27.5"	29"	29"	29"	29"	29"

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.