



SPECIFIKACIJE

OKVIR	
VELIKOSTI	27.5: XS,S,M,L, 29: S,M,L,XL,XXL
BARVE	Black, Hematite
OKVIR	ALUXX-Grade Aluminum, disc
VILICE	SXC32-2 RL, air spring, QR, alloy steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M: 100mm travel (27.5) / 100mm travel (29) L: 100mm travel (27.5) / 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Connect Trail, 31.8mm XS: 730mm (27.5) S: 780mm (27.5) / 780mm (29) M: 780mm (27.5) / 780mm travel (29) L: 780mm (27.5) / 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIPS	Giant Sole-O
OPORA KRMILA	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (27.5) / 60mm travel (29) L: 70mm (27.5) / 70mm (29) XL: 80mm (29) XXL: 90mm (29)
OPORA SEDEŽA	Giant Sport, 30.9 XS: 300mm (27.5) S: 300mm (27.5) / 375mm (29) M: 375mm (27.5) / 375mm travel (29) L: 375mm (27.5) / 375mm (29) XL: 375mm (29) XXL: 375mm (29)
SEDEŽ	Giant custom
PEDALA	MTB caged
POGON	
PRESTAVNE ROČICE	Shimano Deore M4100, 1x10
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano Deore M5120
ZAVORE	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Tektro HDC M275
VERIŽNIK	Shimano Deore M4100, 11x42
VERIGA	KMC X10
GONILKE Z VERIŽNIKI	ProWheel Charm, 30t (27.5) or 32t (29) XS: 165mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (27.5) / 175mm travel (29) L: 175mm (27.5) / 175mm (29) XL: 175mm (29) XXL: 175mm (29)
BOTTOM BRACKET	cartridge

OBROČNIKI	
OBROČI	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
PESTA	alloy, sealed bearing
NAPERE	stainless, 14g
PLAŠČI	Kenda Booster 27.5 or 29x2.4", wire bead
DODATKI	2.4" max tire size

GEOMETRIJA

OKVIR	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (27.5")	L (29")	XL (29")	XXL (29")
Dolžina sedežne cevi (mm)	350	385	390	430	440	490	490	535	565
Kot sedežne cevi	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°
Top Tube Length (mm)	544	569	577	597	599	618	620	639	658
Višina glave okvirja (mm)	95	115	95	130	105	155	125	140	155
Krmilni kot	67,5°	67,5°	68,5°	67,5°	68,5°	67,5°	68,5°	68,5°	68,5°
Zamik vpetja osi (mm)	42	42	51	42	51	42	51	51	51
Trail (mm)	103	103	94	103	94	103	94	94	94
Medosna razdalja (mm)	1079	1106	1126	1137	1150	1162	1172	1192	1213
Dolžina cevi ob verigi (mm)	440	440	455	440	455	440	455	455	455
Bottom Bracket Drop (mm)	45	45	55	45	55	45	55	55	55
Oddaljenost zgornje cevi od gonilne osi (mm)	533	571	602	598	611	621	630	644	658
Doseg (mm)	385	405	404	425	424	440	439	454	469
Višina zgornje cevi (mm)	686	711	732	748	766	794	805	839	856
Širina krmila (mm)	780	780	780	780	780	780	780	780	780
Dolžina opore krmila (mm)	40	50	50	60	60	70	70	80	90
Dolžina gonilke (mm)	165	170	170	175	175	175	175	175	175
Velikost obročnikov	27.5"	27.5"	29"	27.5"	29"	27.5"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.