

TALON 1



SPECS

RAM	
STORLEKAR	27.5: XS,S, 29: S,M,L,XL,XXL
FÄRGER	Metallic Blue, Charcoal
RAM	ALUXX-grade aluminum, disc
GAFFEL	SXC32-3 RL, coil spring, thru axle, steel steerer, 15x110 XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
BAKDÄMPARE	N/A
KOMPONENTER	
STYRE	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GREPPAR	Giant Sole-O
STAM	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SADELSTOLPE	Giant Contact Switch Core, 30.9 XS: 100x350mm (27.5) S: 100x350mm (27.5) / 100x350mm (29) M: 120x400mm (29) L: 120x400mm (29) XL: 120x400mm (29) XXL: 120x400mm (29)
SADEL	Giant ErgoContact Trail
PEDALER	MTB caged
DRIVLINA	
VÄXLAR	Shimano CUES SL-6000, 1x10
FRAMVÄXEL	N/A
BAKVÄXEL	Shimano CUES RD-U6000, clutch
BROMSAR	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
BROMSSPAKAR	Tektro HDC M275
KASSETT	Shimano CUES, CS-LG300, 11x48
KEDJA	KMC X-11
VEVPARTI	ProWheel Charm, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
BROMSREGLAGE	cartridge

HJUL	
FÄLGAR	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NAV	[F] Giant Tracker hub, sealed bearing, 15x110 thru axle. [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
EKRAR	stainless, 14g
DÄCK	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
EXTRAFUNKTIONER	2.4" max tire size

Price: 10 990,00 kr

GEOMETRY

RAM	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Längd sadelrör (mm)	380	420	450	480	500
Seat Post Insertion Depth (mm)	340	200	237	292	322
Vinkel sadelrör	74,5°	74,5°	74,5°	74,5°	74,5°
Topprörets längd (mm)	581	604	629	653	676
Styrhuvud Längd (mm)	95	105	125	140	155
Vinkel styrhuvud	67,5°	67,5°	67,5°	67,5°	67,5°
Gaffelvinkel (mm)	44	44	44	44	44
Spår (mm)	108,9	108,9	108,9	108,9	108,9
Hjulbas (mm)	1139	1164	1191	1217	1242
Kedjestagslängd (mm)	455	455	455	455	455
Nedre fäste Drop (mm)	55	55	55	55	55
Stack (mm)	597	606	625	639	653
Reach (mm)	415	436	456	476	495
Stå över höjden (mm)	715	709	709	710	707
Styrets bredd (mm)	690	690	690	690	690
Stamlängd (mm)	50	60	70	80	90
Vevlängd (mm)	170	170	170	175	175
Hjulstorlek	29"	29"	29"	29"	29"

All specifications listed are subject to change without notice.