



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	27.5: XS,S,M,L, 29: S,M,L,XL,XXL
FARBE	Knight Shield, Phantom Green
RAHMEN	ALUXX-Grade Aluminum, disc
GABEL	SR Suntour XCM30, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29)
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Connect Trail, 31.8mm XS: 730mm (27.5) S: 780mm (27.5) / 780mm (29) M: 780mm (27.5) / 780mm travel (29) L: 780mm (27.5) / 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIFFE	Giant Sole-O
VORBAU	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (27.5) / 60mm travel (29) L: 70mm (27.5) / 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SATTELSTÜTZE	Giant Sport, 30.9 XS: 300mm (27.5) S: 300mm (27.5) / 375mm (29) M: 375mm (27.5) / 375mm travel (29) L: 375mm (27.5) / 375mm (29) XL: 375mm (29) XXL: 375mm (29)
SATTEL	Giant custom
PEDALE	MTB caged
ANTRIEB	
SCHALTHEBEL	Shimano Altus M2010, 2x9
UMWERFER	Shimano Altus M2020
SCHALTWERK	Shimano Altus M2000
BREMSSEN	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
BREMSHEBEL	Tektro HDC M275
KASSETTE	Shimano Deore HG200, 11x32
KETTE	KMC X9
KURBEL	ProWheel forged, 22/36 XS: 165mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (27.5) / 175mm travel (29) L: 175mm (27.5) / 175mm (29) XL: 175mm (29) XXL: 175mm (29)
TRETLAGER	cartridge

LAUFRÄDER	
FELGEN	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NABE	alloy, sealed bearing
SPEICHEN	stainless, 14g
REIFEN	Kenda Booster 27.5 or 29x2.2", wire bead
EXTRAS	2.4" max tire size

GEOMETRIEDATEN

RAHMEN	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (27.5")	L (29")	XL (29")	XXL (29")
Sitzrohrlänge (mm)	350	385	390	430	440	490	490	535	565
Sitzrohrwinkel	74.0°	74.0°	74.0°	74.0°	74.0°	74.0°	74.0°	74.0°	74.0°
Oberrohrlänge (mm)	544	569	577	597	599	618	620	639	658
Steuerrohr-Länge (mm)	95	115	95	130	105	155	125	140	155
Steuerrohr-Winkel	67.5°	67.5°	68.5°	67.5°	68.5°	67.5°	68.5°	68.5°	68.5°
Gabelneigung (mm)	42	42	51	42	51	42	51	51	51
Trail (mm)	103	103	94	103	94	103	94	94	94
Radstand (mm)	1079	1106	1126	1137	1150	1162	1172	1192	1213
Kettenstreben-Länge (mm)	440	440	455	440	455	440	455	455	455
Tretlager-Höhe (mm)	45	45	55	45	55	45	55	55	55
Stack (mm)	533	571	602	598	611	621	630	644	658
Reach (mm)	385	405	404	425	424	440	439	454	469
Überstandshöhe (mm)	686	711	732	748	766	794	805	839	856
Lenkerbreite (mm)	780	780	780	780	780	780	780	780	780
Vorbaulänge (mm)	40	50	50	60	60	70	70	80	90
Kurbellänge (mm)	165	170	170	175	175	175	175	175	175
Radgrösse	27.5"	27.5"	29"	27.5"	29"	27.5"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.