



## SPEZIFIKATIONEN

RAHMEN & GABEL	
RAHMENGRÖSSEN	27.5: XS,S, 29: S,M,L,XXL
FARBE(N)	Asphalt Green
RAHMEN	ALUXX-grade aluminum, disc
GABEL	SXC32-3 RL, coil spring, thru axle, steel steerer, 15x110 XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
DÄMPFER	N/A
COCKPIT	
LENKER	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIFFE	Giant Sole-O
VORBAU	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SATTELSTÜTZE	Giant Sport, 30.9 XS: 350mm (27.5) S: 350mm (27.5) / 375mm (29) M: 375mm (29) L: 375mm (29) XL: 420mm (29) XXL: 420mm (29)
SATTEL	Giant ErgoContact Trail
PEDALE	MTB caged
SCHALTUNG, ANTRIEB	
SCHALTHEBEL	microSHIFT Advent, 1x9
UMWERFER	N/A
SCHALTWERK	microSHIFT Advent, clutch
BREMSEN	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
BREMSHEBEL	Tektro HDC M275
KASSETTE	microSHIFT, 11x46
KETTE	KMC X-9
KURBELSATZ	ProWheel Charm, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
INNENLAGER	cartridge

LAUFRÄDER	
FELGEN	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NABEN (V/H)	[F] Giant Tracker hub, sealed bearing, 15x110 thru axle. [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
SPEICHEN	stainless, 14g
REIFEN	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
ZUBEHÖR (TEILW. VERBAUT)	2.4" max tire size

UVP: 699,00 €

## GEOMETRIEDATEN

RAHMEN & GABEL	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Sitzrohrlänge (mm)	345	375	380	420	450	480	500
Einstecktiefe der Sattelstütze (mm)	306	337	340	200	237	292	322
Sitzwinkel	74,0°	74,0°	74,5°	74,5°	74,5°	74,5°	74,5°
Oberrohrlänge (mm)	542	562	581	604	629	653	676
Steuerrohrlänge (mm)	90	90	95	105	125	140	155
Lenkwinkel	67,0°	67,0°	67,5°	67,5°	67,5°	67,5°	67,5°
Gabelvorbiegung (mm)	44	44	44	44	44	44	44
Gabelnachlauf (mm)	105,2	105,2	108,9	108,9	108,9	108,9	108,9
Radstand (mm)	1084	1104	1139	1164	1191	1217	1242
Kettenstrebeneblänge (mm)	440	440	455	455	455	455	455
Tretlagerabsenkung (mm)	45	45	55	55	55	55	55
Stack (mm)	548	548	597	606	625	639	653
Reach (mm)	385	405	415	436	456	476	495
Überstands-/Durchstiegshöhe (mm)	684	684	715	709	709	710	707
Lenkerbreite (mm)	690	690	690	690	690	690	690
Vorbaulänge (mm)	40	50	50	60	70	80	90
Kurbelarmlänge (mm)	170	165	170	170	170	175	175
Raddurchmesser	27.5"	27.5"	29"	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.