



TECHNIQUES

CADRE	
TAILLES	27.5: XS,S,M,L, 29: S,M,L,XL,XXL
COLORIS	Knight Shield, Phantom Green
CADRE	ALUXX-Grade Aluminum, disc
FOURCHE	SR Suntour XCM30, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29)
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Connect Trail, 31.8mm XS: 730mm (27.5) S: 780mm (27.5) / 780mm (29) M: 780mm (27.5) / 780mm travel (29) L: 780mm (27.5) / 780mm (29) XL: 780mm (29) XXL: 780mm (29)
POIGNÉES	Giant Sole-O
POTENCE	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (27.5) / 60mm travel (29) L: 70mm (27.5) / 70mm (29) XL: 80mm (29) XXL: 90mm (29)
TIGE DE SELLE	Giant Sport, 30.9 XS: 300mm (27.5) S: 300mm (27.5) / 375mm (29) M: 375mm (27.5) / 375mm travel (29) L: 375mm (27.5) / 375mm (29) XL: 375mm (29) XXL: 375mm (29)
SELLE	DDK GP100M TEM99 BLACK STEEL BLACK WITH BUMPER BLACK DECAL
PÉDALES	MTB caged
DÉRAILLEUR	
MANETTES	Shimano Altus M2010, 2x9
DÉRAILLEUR AVANT	Shimano Altus M2020
DÉRAILLEUR ARRIÈRE	Shimano Altus M2000
FREINS	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
LEVIERS DE FREIN	Tektro HDC M275
CASSETTE	Shimano Deore HG200, 11x32
CHAÎNE	KMC X9
PÉDALIER	ProWheel forged, 22/36 XS: 165mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (27.5) / 175mm travel (29) L: 175mm (27.5) / 175mm (29) XL: 175mm (29) XXL: 175mm (29)
BOITIER DE PÉDALIER	cartridge

ROUES	
JANTES	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
MOYEUX	alloy, sealed bearing
RAYONS	stainless, 14g
PNEUS	Kenda Booster 27.5 or 29x2.2", wire bead
EXTRAS	2.4" max tire size
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 599,00 €

GÉOMÉTRIE

CADRE	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")
Longueur de tube de selle (mm)	350	385	390	440	490	535
Angle de tube de selle	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°
Longueur du tube supérieur (mm)	544	569	577	599	620	639
Longueur du tube de direction (mm)	95	115	95	105	125	140
Angle du tube de direction	67,5°	67,5°	68,5°	68,5°	68,5°	68,5°
Déport de fourche (mm)	42	42	51	51	51	51
Trail (mm)	103	103	94	94	94	94
Empattement (mm)	1079	1106	1126	1150	1172	1192
Longueur des bases (mm)	440	440	455	455	455	455
Drop du boîtier de pédalier (mm)	45	45	55	55	55	55
Stack (mm)	533	571	602	611	630	644
Reach (mm)	385	405	404	424	439	454
Hauteur en statique (mm)	686	711	732	766	805	839
Largeur de cintre (mm)	780	780	780	780	780	780
Longueur de potence (mm)	40	50	50	60	70	80
Longueur des manivelles (mm)	165	170	170	175	175	175
Diamètre des roues	27.5"	27.5"	29"	29"	29"	29"

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.