



SPECIFICATIES

FRAME	
MATEN	29: S,M,L,XXL
KLEUREN	Asphalt Green, Dried Matcha
FRAME	ALUXX-grade aluminum, disc
VOORVORK	SXC32-3 RL, coil spring, thru axle, steel steerer, 15x110 XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
HANDVATTEN	Giant Sole-O
STUURPEN	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
ZADELPEN	Giant Sport, 30.9 XS: 350mm (27.5) S: 350mm (27.5) / 375mm (29) M: 375mm (29) L: 375mm (29) XL: 420mm (29) XXL: 420mm (29)
ZADEL	Giant ErgoContact Trail
PEDALEN	MTB caged
AFMONTAGE	
SHIFTERS	microSHIFT Advent, 1x9
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	microSHIFT Advent, clutch
REMMEN	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
REMHENDELS	Tektro HDC M275
CASSETTE	microSHIFT, 11x46
AANDRIJVING	KMC X-9
CRANKSET	ProWheel Charm, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
BOTTOM BRACKET	cartridge

WIELSET	
VELGEN	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NAVEN	[F] Giant Tracker hub, sealed bearing, 15x110 thru axle. [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
SPAKEN	stainless, 14g
BANDEN	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
EXTRA'S	2.4" max tire size

Adviesprijs: € 699,00

GEOMETRIE

FRAME	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Zitbuis lengte (mm)	380	420	450	480	500
Seat Post Insertion Depth (mm)	340	200	237	292	322
Zitbuis hoek	74,5°	74,5°	74,5°	74,5°	74,5°
Frame Lengte (horizontaal) (mm)	581	604	629	653	676
Balhoofdbuis Lengte (mm)	95	105	125	140	155
Balhoofdbuis Hoek	67,5°	67,5°	67,5°	67,5°	67,5°
Vork Sprong (mm)	44	44	44	44	44
Naloop (mm)	108,9	108,9	108,9	108,9	108,9
Wielbasis (mm)	1139	1164	1191	1217	1242
Liggende achtervork lengte (mm)	455	455	455	455	455
Bottom Bracket Drop (mm)	55	55	55	55	55
Stack (mm)	597	606	625	639	653
Reach (mm)	415	436	456	476	495
Stand Over Height (mm)	715	709	709	710	707
Stuur breedte (mm)	690	690	690	690	690
Stuurpen Lengte (mm)	50	60	70	80	90
Cranklengte (mm)	170	170	170	175	175
Wielmaat	29"	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.