

TALON 2



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	27.5: XS,S, 29: S,M,L,XXL
FARBY	Phoenix Fire, Eclipse, Icicle White
RÁM	ALUXX-grade aluminum, disc
VIDLICA	SXC32-3 RL, coil spring, thru axle, steel steerer, 15x110 XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
KOMONENTY	
RIADIDLÁ	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIPY	Giant Sole-O
PREDSTAVEC	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SEDOVKA	Giant Sport, 30.9 XS: 350mm (27.5) S: 350mm (27.5) / 375mm (29) M: 375mm (29) L: 375mm (29) XL: 420mm (29) XXL: 420mm (29)
SEDADLO	Giant ErgoContact Trail
PEDÁLE	MTB caged
POHON	
RADENIE	microSHIFT Advent, 1x9
PREHADZOVAČKA	microSHIFT Advent, clutch
BRZDY	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
BRZDOVÉ PÁKY	Tektro HDC M275
KAZETA	microSHIFT, 11x46
REŤAZ	KMC X9
KLUKY	ProWheel Charm, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
STREDOVÉ ZLOŽENIE	cartridge

KOLESÁ	
RÁFIKY	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NÁBOJE	[F] Giant Tracker hub, sealed bearing, 15x110 thru axle. [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
ŠPICE	stainless, 14g
PNEUMATIKY	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
LIMITY	
MAXIMÁLNA ŠÍRKA PNEUMATÍK	2.4" max tire size
MAXIMÁLNA VEĽKOSŤ REŤAZE	32T

Cena: 829 €

GEOMETRIA

RÁM	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Dĺžka sedlovej trubky (mm)	345	375	380	420	450	480	500
Hĺbka vloženia sedlovky (mm)	300	340	245	200	250	300	330
Uhol sedlovej trubky	74,0°	74,0°	74,5°	74,5°	74,5°	74,5°	74,5°
Dĺžka hornej rámovej trubky (mm)	542	562	581	604	629	653	676
Dĺžka hlavovej trubky (mm)	90	90	95	105	125	140	155
Uhol hlavovej trubky	67,0°	67,0°	67,5°	67,5°	67,5°	67,5°	67,5°
Offset vidlice (mm)	44	44	44	44	44	44	44
Trail (mm)	105	105	109	109	109	109	109
Rázvor (mm)	1084	1104	1140	1164	1191	1216	1242
Dĺžka zadnej stavby (mm)	440	440	455	455	455	455	455
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	45	45	55	55	55	55	55
Stack - výška riadenia (mm)	548	548	597	606	625	638	652
Reach (mm)	385	405	415	435	455	475	495
Výška rámu od zeme (mm)	684	684	715	708	708	710	707
Šírka riaditok (mm)	760	760	760	760	760	760	760
Dĺžka predstavca (mm)	40	50	40	50	60	60	80
Dĺžka klúku (mm)	165	165	170	170	170	175	175

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.