



SPECS

FRAME	
SIZES	27.5: XS,S,M,L, 29: S,M,L,XL,XXL
COLORS	Good Gray, Amber Glow, Black Chrome
FRAME	ALUXX-Grade Aluminum, disc
FORK	SR Suntour XCE, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29)
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 31.8mm XS: 640mm (27.5) S: 640mm (27.5) / 780mm (29) M: 670mm (27.5) / 780mm travel (29) L: 780mm (27.5) / 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIPS	Giant Sole-O
STEM	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (27.5) / 60mm travel (29) L: 70mm (27.5) / 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SEATPOST	Giant Sport, 30.9 XS: 300mm (27.5) S: 300mm (27.5) / 375mm (29) M: 375mm (27.5) / 375mm travel (29) L: 375mm (27.5) / 375mm (29) XL: 375mm (29) XXL: 375mm (29)
SADDLE	Giant custom
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	microSHIFT, 2x8
FRONT DERAILLEUR	microSHIFT FD-M282
REAR DERAILLEUR	Shimano Altus M310
BRAKES	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
BRAKE LEVERS	Tektro HDC M275
CASSETTE	Shimano Deore HG200, 12x32
CHAIN	KMC 8.3
CRANKSET	Shimano FC-M315, 22/36 XS: 170mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (27.5) / 175mm travel (29) L: 175mm (27.5) / 175mm (29) XL: 175mm (29) XXL: 175mm (29)
BOTTOM BRACKET	cartridge

WHEELS

RIMS	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
HUBS	alloy, sealed bearing
SPOKES	stainless, 14g
TIRES	Kenda Booster 27.5 or 29x2.2", wire bead
EXTRAS	2.4" max tire size

GEOMETRY

FRAME	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (27.5")	L (29")	XL (29")
Seat Tube Length (mm)	350	385	390	430	440	490	490	535
Seat Tube Angle	74.0°	74.0°	74.0°	74.0°	74.0°	74.0°	74.0°	74.0°
Top Tube Length (mm)	544	569	577	597	599	618	620	639
Head Tube Length (mm)	95	115	95	130	105	155	125	140
Head Tube Angle	67.5°	67.5°	68.5°	67.5°	68.5°	67.5°	68.5°	68.5°
Fork Rake (mm)	42	42	51	42	51	42	51	51
Trail (mm)	103	103	94	103	94	103	94	94
Wheelbase (mm)	1079	1106	1126	1137	1150	1162	1172	1192
Chain Stay Length (mm)	440	440	455	440	455	440	455	455
Bottom Bracket Drop (mm)	45	45	55	45	55	45	55	55
Stack (mm)	533	571	602	598	611	621	630	644
Reach (mm)	385	405	404	425	424	440	439	454
Stand Over Height (mm)	686	711	732	748	766	794	805	839
Handlebar Width (mm)	780	780	780	780	780	780	780	780
Stem Length (mm)	40	50	50	60	60	70	70	80
Crank Length (mm)	165	170	170	175	175	175	175	175
Wheel Size	27.5"	27.5"	29"	27.5"	29"	27.5"	29"	29"

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.