TALON 3



TEKNISET TIEDOT

RUNKO	
KOOT	27.5: XS, S; 29: S, M, L, XL, XXL
VÄRIT	Pangea Green, Orange, Liquid Metal
RUNKO	ALUXX-grade aluminum, disc
HAARUKKA	SR Suntour XCE, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
KOMPONENTIT	
OHJAUSTANKO	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIPIT	Giant Sole-O
OHJAINKANNATIN	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SATULATOLPPA	Giant Sport, 30.9 XS: 350mm (27.5) S: 350mm (27.5) / 375mm (29) M: 375mm (29) L: 375mm (29) XL: 420mm (29) XXL: 420mm (29)
SATULA	Giant ErgoContact Trail
POLKIMET	MTB caged
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Altus, 2x8
ETUVAIHTAJA	Shimano Altus
TAKAVAIHTAJA	Shimano Acera
JARRUT	Tektro HD M3121, hydraulic, Tektro rotors [F]180mm, [R]160mm
JARRUKAHVAT	Tektro HD M3121
RATASPAKKA	Shimano Altus HG31, 11x34
KETJUT	KMC 8.3
KAMPISARJA	Shimano Altus FC-M315, 22/36 XS: 170mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
KESKIÖ	cartridge

RENKAAT	
VANTEET	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NAVAT	[F] QR alloy, sealed bearing, [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
PINNAT	stainless, 14g
RENKAAT	Maxxis Ikon 27.5x2.2 or Maxxis Ikon 29x2.2, wire bead
RAJOITTEET	
MAX RENGASVARA	2.4"
MAX KETJUN KOKO	32T

Suositushinta: 689,00 €

GEOMETRIA

RUNKO	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Satulaputken pituus (mm)	345	375	380	420	450	480	500
Satulatolpan asennussyvyys (mm)	300	340	245	200	250	300	330
Satulaputken kulma	74,0°	74,0°	74,5°	74,5°	74,5°	74,5°	74,5°
Vaakaputken pituus (mm)	542	562	581	604	629	653	676
Emäputken pituus (mm)	90	90	95	105	125	140	155
Emäputken kulma	67,0°	67,0°	67,5°	67,5°	67,5°	67,5°	67,5°
Haarukan offset (mm)	44	44	44	44	44	44	44
Trail-mitta (mm)	105	105	109	109	109	109	109
Akseliväli (mm)	1084	1104	1140	1164	1191	1216	1242
Takahaarukan alaputken pituus (mm)	440	440	455	455	455	455	455
Keskiön pudotus (mm)	45	45	55	55	55	55	55
Stack-mitta (mm)	548	548	597	606	625	638	652
Reach-mitta (mm)	385	405	415	435	455	475	495
Standover-mitta (mm)	684	684	715	708	708	710	707
Ohjaustangon leveys (mm)	760	760	760	760	760	760	760
Ohjainkannattimen pituus (mm)	40	50	40	50	60	60	80
Kammen pituus (mm)	165	165	170	170	170	175	175

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.