

TALON 3



TECHNIQUES

CADRE	
TAILLES	27.5: XS, S; 29: S, M, L, XL, XXL
COLORIS	Pangea Green, Orange
CADRE	ALUXX-grade aluminum, disc
FOURCHE	SR Suntour XCE, coil spring, straight steerer XS: 80mm (27.5) S: 80mm (27.5) / 100mm (29) M: 100mm (29) L: 100mm (29) XL: 100mm (29) XXL: 100mm (29)
COMPOSANTS	
CINTRE	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
POIGNÉES	Giant Sole-O
POTENCE	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
TIGE DE SELLE	Giant Sport, SP217, 30.9 XS: 350mm (27.5) S: 350mm (27.5) / 375mm (29) M: 375mm (29) L: 375mm (29) XL: 420mm (29) XXL: 420mm (29)
SELLE	Giant ErgoContact Trail
PÉDALES	MTB caged, 9/16" (nylon body, steel cage)
DÉRAILLEUR	
MANETTES	Shimano Acera/Altus 2x8, SL-M315-2L / SL-M315-8R
DÉRAILLEUR AVANT	Shimano Acera/Altus, FD-M315-TS
DÉRAILLEUR ARRIÈRE	Shimano Acera, RD-M3020-8, 2x8
FREINS	Tektro HDC M275, hydraulic, Tektro rotors [F] 180mm, [R] 160mm
LEVIER DE FREIN	Tektro HDC M275
CASSETTE	Shimano Acera/Altus, CS-HG31-8, 11-34, 8-speed
CHAÎNE	KMC 8.3
PÉDALIER	Shimano Acera/Altus, FC-M315-2, 36-22T, 48.8mm chainline XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
BOITIER DE PÉDALIER	(B1210-VPBC73-) cartridge

ROUES	
JANTES	Giant GX03V 29/27.5, 6061 aluminum, double wall, 21mm inner width, disc, 28h
MOYEUX	[F] Giant Tracker Rear Hub, M9202-F, 6-bolt rotor mount. [R] Giant Tracker Rear Hub, M9201-R, microspine body, HG type. 15x9 QR F / 12x142 9mm QR R
RAYONS	Stainless steel 14G, black
PNEUS	Maxxis Ikon 29x2.2 / Maxxis Ikon 27.5x2.2, 60 TPI, wire bead
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
DÉGAGEMENT MAX DES PNEUS	2.4"
TAILLE MAXIMALE DU PLATEAU	32T

Prix Public Conseillé: 700,00 €

GÉOMÉTRIE

CADRE	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Longueur de tube de selle (mm)	345	375	380	420	450	480	500
Seat Post Insertion Depth (mm)	300	340	245	200	250	300	330
Angle de tube de selle	74,0°	74,0°	74,5°	74,5°	74,5°	74,5°	74,5°
Longueur du tube supérieur (mm)	542	562	581	604	629	653	676
Longueur du tube de direction (mm)	90	90	95	105	125	140	155
Angle du tube de direction	67,0°	67,0°	67,5°	67,5°	67,5°	67,5°	67,5°
Déport de fourche (mm)	44	44	44	44	44	44	44
Trail (mm)	105	105	109	109	109	109	109
Empattement (mm)	1084	1104	1140	1164	1191	1216	1242
Longueur des bases (mm)	440	440	455	455	455	455	455
Drop du boîtier de pédalier (mm)	45	45	55	55	55	55	55
Stack (mm)	548	548	597	606	625	638	652
Reach (mm)	385	405	415	435	455	475	495
Hauteur en statique (mm)	684	684	715	708	708	710	707
Largeur de cintre (mm)	760	760	760	760	760	760	760
Longueur de potence (mm)	40	50	40	50	60	60	80
Longueur des manivelles (mm)	165	165	170	170	170	175	175

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.