

TALON 3



SPECIFICATIES

FRAME	
MATEN	27.5: XS,S, 29: S,M,L,XL,XXL
KLEUREN	Frost Silver, Panther
FRAME	ALUXX-grade aluminum, disc
VOORVORK	SR Suntour XCE, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
HANDVATTEN	Giant Sole-O
STUURPEN	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
ZADELPEN	Giant Sport, 30.9 XS: 350mm (27.5) S: 350mm (27.5) / 375mm (29) M: 375mm (29) L: 375mm (29) XL: 420mm (29) XXL: 420mm (29)
ZADEL	Giant ErgoContact Trail
PEDALEN	MTB caged
AFMONTAGE	
SHIFTERS	Shimano Altus, 2x8
VOORDERAILLEUR	Shimano Altus
ACHTERDERAILLEUR	Shimano Acera
REMMEN	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
REMHENDELS	Tektro HDC M275
CASSETTE	Shimano Altus HG31, 11x34
AANDRIJVING	KMC 8.3
CRANKSET	Shimano Altus FC-M315, 22/36 XS: 170mm (27.5) S: 165mm (27.5) / 170mm (29) M: 175mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
BOTTOM BRACKET	cartridge

WIELSET	
VELGEN	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NAVEN	[F] QR alloy, sealed bearing, [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
SPAKEN	stainless, 14g
BANDEN	Maxxis Ikon 27.5x2.2 or Maxxis Ikon 29x2.2, wire bead
EXTRA'S	2.4" max tire size

Adviesprijs: € 649,00

GEOMETRIE

FRAME	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Zitbuis Lengte (mm)	345	375	380	420	450	480	500
Seat Post Insertion Depth (mm)	306	337	340	200	237	292	322
Zitbuis Hoek	74,0°	74,0°	74,5°	74,5°	74,5°	74,5°	74,5°
Frame Lengte (horizontaal) (mm)	542	562	581	604	629	653	676
Balhoofdbuis Lengte (mm)	90	90	95	105	125	140	155
Balhoofdbuis Hoek	67,0°	67,0°	67,5°	67,5°	67,5°	67,5°	67,5°
Vork Sprong (mm)	44	44	44	44	44	44	44
Naloop (mm)	105,2	105,2	108,9	108,9	108,9	108,9	108,9
Wielbasis (mm)	1084	1104	1139	1164	1191	1217	1242
Liggende achtervork lengte (mm)	440	440	455	455	455	455	455
Bottom Bracket Drop (mm)	45	45	55	55	55	55	55
Stack (mm)	548	548	597	606	625	639	653
Reach (mm)	385	405	415	436	456	476	495
Stand Over Height (mm)	684	684	715	709	709	710	707
Stuur breedte (mm)	690	690	690	690	690	690	690
Stuurpen Lengte (mm)	40	50	50	60	70	80	90
Cranklengte (mm)	170	165	170	170	170	175	175
Wielmaat	27.5"	27.5"	29"	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.