

TALON 3



SPECS

QUADRO	
TAMANHOS	27.5: XS,S 29: S,M,L,XL,XXL
CORES	Amber Glow
QUADRO	ALUXX-Grade Aluminum, disc
FORQUILHA	SR Suntour XCE, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29)
AMORTECEDORES	N/A
COMPONENTES	
GUIADOR	Giant Connect Trail, 31.8mm XS: 640mm (27.5) S: 640mm (27.5) / 780mm (29) M: 670mm (27.5) / 780mm travel (29) L: 780mm (27.5) / 780mm (29) XL: 780mm (29) XXL: 780mm (29)
PUNHOS	Giant Sole-O
AVANÇO	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (27.5) / 60mm travel (29) L: 70mm (27.5) / 70mm (29) XL: 80mm (29) XXL: 90mm (29)
ESPIGÃO DE SELIM	Giant Sport, 30.9 XS: 300mm (27.5) S: 300mm (27.5) / 375mm (29) M: 375mm (27.5) / 375mm travel (29) L: 375mm (27.5) / 375mm (29) XL: 375mm (29) XXL: 375mm (29)
SELIM	Giant custom
PEDAIS	MTB caged
TRANSMISSÃO	
MANETES	microSHIFT, 2x8
DESVIADOR DIANTEIRO	microSHIFT FD-M282
DESVIADOR TRASEIRO	Shimano Altus M310
TRAVÕES	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
MANÍPULOS DOS TRAVÕES	Tektro HDC M275
CASSETTE	Shimano Deore HG200, 12x32
CORRENTE	KMC 8.3
CONJUNTO PEDALEIRO	Shimano FC-M315, 22/36 XS: 170mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (27.5) / 175mm travel (29) L: 175mm (27.5) / 175mm (29) XL: 175mm (29) XXL: 175mm (29)
MOVIMENTO CENTRAL	cartridge

RODAS	
AROS	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
CUBOS	alloy, sealed bearing
RAIOS	stainless, 14g
PNEUS	Kenda Booster 27.5 or 29x2.2", wire bead
EXTRAS	2.4" max tire size

Preço: 599,00 €

GEOMETRIA

QUADRO	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Comprimento do tubo do assento (mm)	350	385	390	440	490	535	565
Ângulo do tubo do assento	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°
Comprimento do tubo superior (mm)	544	569	577	599	620	639	658
Comprimento do tubo principal (mm)	95	115	95	105	125	140	155
Ângulo do tubo principal	67,5°	67,5°	68,5°	68,5°	68,5°	68,5°	68,5°
Garfo ancinho (mm)	42	42	51	51	51	51	51
Trilha (mm)	103	103	94	94	94	94	94
distância entre eixos (mm)	1079	1106	1126	1150	1172	1192	1213
Comprimento Chain Stay (mm)	440	440	455	455	455	455	455
Suporte inferior (mm)	45	45	55	55	55	55	55
Pilha (mm)	533	571	602	611	630	644	658
Alcançar (mm)	385	405	404	424	439	454	469
Altura do standover (mm)	686	711	732	766	805	839	856
Largura do guidão (mm)	780	780	780	780	780	780	780
Comprimento da haste (mm)	40	50	50	60	70	80	90
Comprimento da Manivela (mm)	165	170	170	175	175	175	175
Tamanho da roda	27.5"	27.5"	29"	29"	29"	29"	29"

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.