TALON 3



SPECIFIKACIJE

OKVIR	
VELIKOSTI	27.5: XS, S; 29: S, M, L, XL, XXL
BARVE	Pangea Green, Orange, Liquid Metal
OKVIR	ALUXX-grade aluminum, disc
VILICE	SR Suntour XCE, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
KOMPONENTE	
KRMILO	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIPS	Giant Sole-O
OPORA KRMILA	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
OPORA SEDEŽA	Giant Sport, 30.9 XS: 350mm (27.5) S: 350mm (27.5) / 375mm (29) M: 375mm (29) L: 375mm (29) XL: 420mm (29) XXL: 420mm (29)
SEDEŽ	Giant ErgoContact Trail
PEDALA	MTB caged
POGON	
PRESTAVNE ROČICE	Shimano Altus, 2x8
PREDNJI MENJALNIK	Shimano Altus
ZADNJI MENJALNIK	Shimano Acera
ZAVORE	Tektro HD M3121, hydraulic, Tektro rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Tektro HD M3121
VERIŽNIK	Shimano Altus HG31, 11x34
VERIGA	KMC 8.3
GONILKE Z VERIŽNIKI	Shimano Altus FC-M315, 22/36 XS: 170mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
BOTTOM BRACKET	cartridge

OBROČNIKI	
OBROČI	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
PESTA	[F] QR alloy, sealed bearing, [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
NAPERE	stainless, 14g
PLAŠČI	Maxxis Ikon 27.5x2.2 or Maxxis Ikon 29x2.2, wire bead
LIMITS	
MAX TIRE CLEARANCE	2.4"
MAX CHAINRING SIZE	32T

GEOMETRIJA

OKVIR	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Dolžina sedežne cevi (mm)	345	375	380	420	450	480	500
Seat Post Insertion Depth (mm)	300	340	245	200	250	300	330
Kot sedežne cevi	74,0°	74,0°	74,5°	74,5°	74,5°	74,5°	74,5°
Top Tube Length (mm)	542	562	581	604	629	653	676
Višina glave okvirja (mm)	90	90	95	105	125	140	155
Krmilni kot	67,0°	67,0°	67,5°	67,5°	67,5°	67,5°	67,5°
Zamik vpetja osi (mm)	44	44	44	44	44	44	44
Trail (mm)	105	105	109	109	109	109	109
Medosna razdalja (mm)	1084	1104	1140	1164	1191	1216	1242
Dolžina cevi ob verigi (mm)	440	440	455	455	455	455	455
Bottom Bracket Drop (mm)	45	45	55	55	55	55	55
Oddaljenost zgornje cevi od gonilne osi (mm)	548	548	597	606	625	638	652
Doseg (mm)	385	405	415	435	455	475	495
Višina zgornje cevi (mm)	684	684	715	708	708	710	707
Širina krmila (mm)	760	760	760	760	760	760	760
Dolžina opore krmila (mm)	40	50	40	50	60	60	80
Dolžina gonilke (mm)	165	165	170	170	170	175	175

Vse navedene specifikacije se lahko spremenijo brez obvestila.