

TALON 3



SPECS

RAM	
STORLEKAR	27.5: XS,S, 29: S,M,L,XL,XXL
FÄRGER	Frost Silver, Beeswax, Panther
RAM	ALUXX-grade aluminum, disc
GAFFEL	SR Suntour XCE, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
BAKDÄMPARE	N/A
KOMPONENTER	
STYRE	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GREPPAR	Giant Sole-O
STAM	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SADELSTOLPE	Giant Sport, 30.9 XS: 350mm (27.5) S: 350mm (27.5) / 375mm (29) M: 375mm (29) L: 375mm (29) XL: 420mm (29) XXL: 420mm (29)
SADEL	Giant ErgoContact Trail
PEDALER	MTB caged
DRIVLINJA	
VÄXLAR	Shimano Altus, 2x8
FRAMVÄXEL	Shimano Altus
BAKVÄXEL	Shimano Acera
BROMSAR	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
BROMSSPAKAR	Tektro HDC M275
KASSETT	Shimano Altus HG31, 11x34
KEDJA	KMC 8.3
VEVPARTI	Shimano Altus FC-M315, 22/36 XS: 170mm (27.5) S: 165mm (27.5) / 170mm (29) M: 175mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
BROMSREGLAGE	cartridge

HJUL	
FÄLGAR	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NAV	[F] QR alloy, sealed bearing, [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
EKRAR	stainless, 14g
DÄCK	Maxxis Ikon 27.5x2.2 or Maxxis Ikon 29x2.2, wire bead
EXTRAFUNKTIONER	2.4" max tire size

Price: 7 890,00 kr

GEOMETRY

RAM	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Längd sadelrör (mm)	345	375	380	420	450	480	500
Seat Post Insertion Depth (mm)	306	337	340	200	237	292	322
Vinkel sadelrör	74,0°	74,0°	74,5°	74,5°	74,5°	74,5°	74,5°
Topprörets längd (mm)	542	562	581	604	629	653	676
Styrhuvud Längd (mm)	90	90	95	105	125	140	155
Vinkel styrhuvud	67,0°	67,0°	67,5°	67,5°	67,5°	67,5°	67,5°
Gaffelvinkel (mm)	44	44	44	44	44	44	44
Spår (mm)	105,2	105,2	108,9	108,9	108,9	108,9	108,9
Hjulbas (mm)	1084	1104	1139	1164	1191	1217	1242
Kedjestagslängd (mm)	440	440	455	455	455	455	455
Nedre fäste Drop (mm)	45	45	55	55	55	55	55
Stack (mm)	548	548	597	606	625	639	653
Reach (mm)	385	405	415	436	456	476	495
Stå över höjden (mm)	684	684	715	709	709	710	707
Styrets bredd (mm)	690	690	690	690	690	690	690
Stamlängd (mm)	40	50	50	60	70	80	90
Vevlängd (mm)	170	165	170	170	170	175	175
Hjulstorlek	27.5"	27.5"	29"	29"	29"	29"	29"

All specifications listed are subject to change without notice.