



SPECS

FRAME	
SIZES	27.5: XS,S, 29: S,M,L,XL,XXL
COLORS	Frost Silver, Beeswax, Panther
FRAME	ALUXX-grade aluminum, disc
FORK	SR Suntour XCE, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIPS	Giant Sole-O
STEM	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SEATPOST	Giant Sport, 30.9 XS: 350mm (27.5) S: 350mm (27.5) / 375mm (29) M: 375mm (29) L: 375mm (29) XL: 420mm (29) XXL: 420mm (29)
SADDLE	Giant ErgoContact Trail
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	Shimano Altus, 2x8
FRONT DERAILLEUR	Shimano Altus
REAR DERAILLEUR	Shimano Acera
BRAKES	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
BRAKE LEVERS	Tektro HDC M275
CASSETTE	Shimano Altus HG31, 11x34
CHAIN	KMC 8.3
CRANKSET	Shimano Altus FC-M315, 22/36 XS: 170mm (27.5) S: 165mm (27.5) / 170mm (29) M: 175mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
BOTTOM BRACKET	cartridge

WHEELS	
RIMS	Giant GX03V 29 or 27.5, alloy, double wall, 21 mm inner width
HUBS	[F] QR alloy, sealed bearing, [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
SPOKES	stainless, 14g
TIRES	Maxxis Ikon 27.5x2.2 or Maxxis Ikon 29x2.2, wire bead
EXTRAS	2.4" max tire size

GEOMETRY

FRAME	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Seat Tube Length (mm)	345	375	380	420	450	480	500
Seat Post Insertion Depth (mm)	306	337	340	200	237	292	322
Seat Tube Angle	74.0°	74.0°	74.5°	74.5°	74.5°	74.5°	74.5°
Top Tube Length (mm)	542	562	581	604	629	653	676
Head Tube Length (mm)	90	90	95	105	125	140	155
Head Tube Angle	67.0°	67.0°	67.5°	67.5°	67.5°	67.5°	67.5°
Fork Rake (mm)	44	44	44	44	44	44	44
Trail (mm)	105.2	105.2	108.9	108.9	108.9	108.9	108.9
Wheelbase (mm)	1084	1104	1139	1164	1191	1217	1242
Chain Stay Length (mm)	440	440	455	455	455	455	455
Bottom Bracket Drop (mm)	45	45	55	55	55	55	55
Stack (mm)	548	548	597	606	625	639	653
Reach (mm)	385	405	415	436	456	476	495
Stand Over Height (mm)	684	684	715	709	709	710	707
Handlebar Width (mm)	690	690	690	690	690	690	690
Stem Length (mm)	40	50	50	60	70	80	90
Crank Length (mm)	170	165	170	170	170	175	175
Wheel Size	27.5"	27.5"	29"	29"	29"	29"	29"

All specifications listed are subject to change without notice.