

TALON 4



SPECS

FRAME	
SIZES	27.5: XS, S; 29: S, M, L, XL, XXL
COLOURS	Azure Blue, Black, Cyber Lime
FRAME	ALUXX-grade aluminum, disc
FORK	SR Suntour XCE, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIPS	Giant Sole-O
STEM	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SEATPOST	Giant Sport, 30.9 XS: 350mm (27.5) S: 350mm (27.5) / 375mm (29) M: 375mm (29) L: 375mm (29) XL: 420mm (29) XXL: 420mm (29)
SADDLE	Giant ErgoContact Trail
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	microSHIFT Acolyte, 1x8
REAR DERAILLEUR	microSHIFT Acolyte, clutch
BRAKES	Tektro 176, hydraulic, Tektro rotors [F]160mm, [R]160mm
BRAKE LEVERS	Tektro TBK 176, hydraulic
CASSETTE	microSHIFT, 12x46
CHAIN	KMC 8.1
CRANKSET	ProWheel Forged, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
BOTTOM BRACKET	cartridge

WHEELS	
RIMS	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
HUBS	[F] QR alloy, sealed bearing, [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
SPOKES	stainless, 14g
TIRES	Maxxis Ikon 27.5x2.2 or Maxxis Ikon 29x2.2, wire bead
LIMITS	
MAX TIRE CLEARANCE	2.4"
MAX CHAINRING SIZE	32T

Suggested Retail Price (CDN): \$749.00

FRAME GEOMETRY

FRAME	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")	XXL (29")
Seat Tube Length (mm)	345	375	380	420	450	480	500
Seat Post Insertion Depth (mm)	300	340	245	200	250	300	330
Seat Tube Angle	74.0°	74.0°	74.5°	74.5°	74.5°	74.5°	74.5°
Top Tube Length (mm)	542	562	581	604	629	653	676
Head Tube Length (mm)	90	90	95	105	125	140	155
Head Tube Angle	67.0°	67.0°	67.5°	67.5°	67.5°	67.5°	67.5°
Fork Rake (mm)	44	44	44	44	44	44	44
Trail (mm)	105	105	109	109	109	109	109
Wheelbase (mm)	1084	1104	1140	1164	1191	1216	1242
Chain Stay Length (mm)	440	440	455	455	455	455	455
Bottom Bracket Drop (mm)	45	45	55	55	55	55	55
Stack (mm)	548	548	597	606	625	638	652
Reach (mm)	385	405	415	435	455	475	495
Stand Over Height (mm)	684	684	715	708	708	710	707
Handlebar Width (mm)	760	760	760	760	760	760	760
Stem Length (mm)	40	50	40	50	60	60	80
Crank Length (mm)	165	165	170	170	170	175	175

All prices and specifications are subject to change without notice.