

TALON 4



SPECS

| FRAME | |
|-------------------------|--|
| SIZES | 27.5: XS,S, 29: S,M,L,XXL |
| COLORS | Radiant Orange, Black |
| FRAME | ALUXX-grade aluminum, disc |
| FORK | SR Suntour XCE, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29) |
| SHOCK | N/A |
| COMPONENTS | |
| HANDLEBAR | Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29) |
| GRIPS | Giant Sole-O |
| STEM | Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29) |
| SEATPOST | Giant Sport, 30.9 XS: 350mm (27.5) S: 350mm (27.5) / 375mm (29) M: 375mm (29) L: 375mm (29) XL: 420mm (29) XXL: 420mm (29) |
| SADDLE | Giant ErgoContact Trail |
| PEDALS | MTB caged |
| DRIVETRAIN | |
| SHIFTERS | microSHIFT Acolyte, 1x8 |
| FRONT DERAILLEUR | N/A |
| REAR DERAILLEUR | microSHIFT Acolyte, clutch |
| BRAKES | Tektro 172, mechanical, Tektro rotors [F]160mm, [R]160mm |
| BRAKE LEVERS | Tektro TBK 172, mechanical |
| CASSETTE | microSHIFT, 12x46 |
| CHAIN | KMC 8.1 |
| CRANKSET | ProWheel Forged, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 175mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29) |
| BOTTOM BRACKET | cartridge |

| WHEELS | |
|---------------|--|
| RIMS | Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width |
| HUBS | [F] QR alloy, sealed bearing, [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive |
| SPOKES | stainless, 14g |
| TIRES | Maxxis Ikon 27.5x2.2 or Maxxis Ikon 29x2.2, wire bead |
| EXTRAS | 2.4" max tire size |

Recommended Retail Price: \$650.00

GEOMETRY

| FRAME | XS (27.5") | S (29") | M (29") | L (29") | XL (29") |
|----------------------------------|------------|---------|---------|---------|----------|
| Seat Tube Length (inch) | 13.6 | 15 | 16.5 | 17.7 | 18.9 |
| Seat Post Insertion Depth (inch) | 12 | 13.4 | 7.9 | 9.3 | 11.5 |
| Seat Tube Angle | 74.0° | 74.5° | 74.5° | 74.5° | 74.5° |
| Top Tube Length (inch) | 21.3 | 22.9 | 23.8 | 24.8 | 25.7 |
| Head Tube Length (inch) | 3.5 | 3.7 | 4.1 | 4.9 | 5.5 |
| Head Tube Angle | 67.0° | 67.5° | 67.5° | 67.5° | 67.5° |
| Fork Rake (inch) | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 |
| Trail (inch) | 4.1 | 4.3 | 4.3 | 4.3 | 4.3 |
| Wheelbase (inch) | 42.7 | 44.8 | 45.8 | 46.9 | 47.9 |
| Chain Stay Length (inch) | 17.3 | 17.9 | 17.9 | 17.9 | 17.9 |
| Bottom Bracket Drop (inch) | 1.8 | 2.2 | 2.2 | 2.2 | 2.2 |
| Stack (inch) | 21.6 | 23.5 | 23.9 | 24.6 | 25.2 |
| Reach (inch) | 15.2 | 16.3 | 17.2 | 18 | 18.7 |
| Stand Over Height (inch) | 26.9 | 28.1 | 27.9 | 27.9 | 28 |
| Handlebar Width (inch) | 27.2 | 27.2 | 27.2 | 27.2 | 27.2 |
| Stem Length (inch) | 1.6 | 2 | 2.4 | 2.8 | 3.1 |
| Crank Length (inch) | 6.7 | 6.7 | 6.7 | 6.7 | 6.9 |
| Wheel Size | 27.5" | 29" | 29" | 29" | 29" |

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*