

TALON 4



ESPECIFICACIONES

CUADRO	
TALLAS	27.5: XS,S, 29: S,M,L,XL,XXL
COLORES	Radiant Orange, Black
CUADRO	ALUXX-grade aluminum, disc
TIJERA	SR Suntour XCE, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIPS	Giant Sole-O
POTENCIA	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
POSTE DE ASIENTO	Giant Sport, 30.9 XS: 350mm (27.5) S: 350mm (27.5) / 375mm (29) M: 375mm (29) L: 375mm (29) XL: 420mm (29) XXL: 420mm (29)
ASIENTO	Giant ErgoContact Trail
PEDALES	MTB caged
TRANSMISIÓN	
MANETAS DE CAMBIO	microSHIFT Acolyte, 1x8
DESVIADOR	N/A
CAMBIO TRASERO	microSHIFT Acolyte, clutch
FRENOS	Tektro 172, mechanical, Tektro rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	Tektro TBK 172, mechanical
CASSETTE	microSHIFT, 12x46
CADENA	KMC 8.1
MULTIPLICACIÓN	ProWheel Forged, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 175mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
EJE DE CENTRO	cartridge

RUEDAS	
RUEDAS	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
MAZAS	[F] QR alloy, sealed bearing, [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
RAYOS	stainless, 14g
NEUMÁTICOS	Maxxis Ikon 27.5x2.2 or Maxxis Ikon 29x2.2, wire bead
EXTRAS	2.4" max tire size

Precio: \$14,490.00

GEOMETRÍA

CUADRO	S (29")	M (29")	L (29")	XL (29")
Longitud de la Base del Poste de Asiento (mm)	380	420	450	480
Seat Post Insertion Depth (mm)	340	200	237	292
Ángulo de la Base del Poste de Asiento	74.5°	74.5°	74.5°	74.5°
Longitud del Tubo Superior (mm)	581	604	629	653
Longitud del Telescopio (mm)	95	105	125	140
Ángulo del Telescopio	67.5°	67.5°	67.5°	67.5°
Rake (mm)	44	44	44	44
Trail (mm)	108.9	108.9	108.9	108.9
Distancia entre Ejes (mm)	1139	1164	1191	1217
Longitud de Vaina Inferior (mm)	455	455	455	455
Caída del Eje de Centro (mm)	55	55	55	55
Stack (mm)	597	606	625	639
Reach (mm)	415	436	456	476
Altura del Tubo Superior al Suelo (mm)	715	709	709	710
Ancho del Manubrio (mm)	690	690	690	690
Longitud de la Potencia (mm)	50	60	70	80
Longitud de la Biela (mm)	170	170	170	175
Tamaño de las Ruedas	29"	29"	29"	29"

Todas las especificaciones están sujetas a cambios sin previo aviso.