TALON E+ 2



SPECIFIKATIONER

E+ SYSTEM	
MOTOR	Giant SyncDrive Sport 3, 85Nm, PedalPlus 6-Sensor technology
KONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, full color LCD display
BATTERI	Giant EnergyPak 430Wh, Giant EnergyPak Plus 200Wh range extender compatible
LADER	Giant EnergyPak 4A smart charger
RAMME	
STØRRELSER	S, M, L, XL
RAMME	ALUXX aluminum, Overdrive 1½ - 1⅛" head tube, integrated KSA40 kickstand mount
FORGAFFEL	SR Suntour XCM32, 100mm travel, 15x110mm thru-axle
KOMPONENTER	
STYR	Giant Connect TR riser 31.8x750mm [S/M], 31.8x780mm [L-XL]
GREB / STYRBÅND	Giant Sole-O
FREMPIND	Giant Contact
SADELPIND	Forged Aluminium, 30.9mm, 2-bolt micro adjustable
SADEL	Giant Ergo Trail ESG
PEDALER	Platform
GEARGRUPPE	
SKIFTEGREB	Shimano CUES, LinkGlide
BAGSKIFTER	Shimano CUES, LinkGlide, 10-speed, Shadow+
BREMSER	Shimano MT-200, hydraulic disc, 180mm [F/R] rotors
BREMSEGREB	Shimano MT-200
KASSETTE	Shimano CUES, LinkGlide, 10-speed, 11x48
KÆDE	Shimano LinkGlide
KRANKSÆT	Forged aluminium, [XS/S] 165mm, [M/L] 170mm, Direct-mount steel, 36t

HJUL	
FÆLGE	Giant GX03V, alloy
NAV	Shimano TC500, Boost, Center-Lock, 15x110mm [F] 12x148mm [R]
EGER	Stainless steel
DÆK	Maxxis Rekon, 29x2.4", wire bead, EXO, 60TPI
TILBEHØR	
SKÆRM / KÆDESKÆRM	Co-molded, 32-38t, adjustable
GRÆNSER	
KOMBINERET MAKSIMAL BELASTNINGSGRÆNSE	150kg

Pris: 20.639,00 kr.

GEOMETRI

RAMME	S	M	L	XL
Sadelrørslængde (mm)	385	435	485	535
Sadelpindindsætningsdybde (mm)	200	240	260	260
Sadelrørsvinkel	74,0°	74,0°	74,0°	74,0°
Overrørslængde (mm)	580	600	620	640
Kronrørslængde (mm)	100	115	130	145
Kronrøsvinkel	68,0°	68,0°	68,0°	68,0°
Forgaffel fremspring (rake) (mm)	46	46	46	46
Sti (mm)	103,9	103,9	103,9	103,9
Akselafstand (mm)	1143	1165	1186	1208
Kædestagslængde (mm)	470	470	470	470
Krankboks drop (mm)	60	60	60	60
Stack (mm)	613	627	641	655
Reach (mm)	404	420	436	452
Skridthøjde (mm)	723	753	788	808
Styrbredde (mm)	750	750	780	780
Frempindslængde (mm)	40	40	50	50
Hjulstørrelse	29"	29"	29"	29"

Alle de anførte specifikationer kan ændres uden varsel.