# TALON E+ 2 EX




## SPECIFICATIES

| | |
|---|---|
| **E+ SYSTEM** | |
| **MOTOR** | Giant SyncDrive Sport 3, 85Nm, PedalPlus 6-Sensor technology |
| **BEDIENINGSUNIT** | Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels |
| **DISPLAY** | Giant RideControl Dash 2, full color LCD display |
| **ACCU** | Giant EnergyPak 430Wh, Giant EnergyPak Plus 200Wh range extender compatible |
| **LADER** | Giant EnergyPak 4A smart charger |
| **FRAME** | |
| **MATEN** | S, M, L, XL |
| **FRAME** | ALUXX aluminum, Overdrive 1½ - 1⅛" head tube, integrated KSA40 kickstand mount |
| **VOORVORK** | SR Suntour XCM32, 100mm travel, 15x110mm thru-axle |
| **ONDERDELEN** | |
| **STUUR** | Giant Connect TR riser 31.8x750mm [S/M], 31.8x780mm [L-XL] |
| **HANDVATTEN** | Giant Sole-O |
| **STUURPEN** | Giant Contact |
| **ZADELPEN** | Forged Aluminium, 30.9mm, 2-bolt micro adjustable |
| **ZADEL** | Giant Ergo Trail ESG |
| **PEDALEN** | platform |
| **AFMONTAGE** | |
| **SHIFTERS** | Shimano CUES, LinkGlide |
| **ACHTERDERAILLEUR** | Shimano CUES, LinkGlide, 10-speed, Shadow+ |
| **REMMEN** | Shimano MT-200, hydraulic disc, 180mm [F/R] rotors |
| **REMHENDELS** | Shimano MT-200 |
| **CASSETTE** | Shimano CUES, LinkGlide, 10-speed, 11x48 |
| **AANDRIJVING** | Shimano LinkGlide |
| **CRANKSET** | Forged aluminium, [XS/S] 165mm, [M/L] 170mm, Direct-mount steel, 36t |

| | |
|---|---|
| **WIELSET** | |
| **VELGEN** | Giant GX03V, alloy |
| **NAVEN** | Shimano TC500, Boost, Center-Lock, 15x110mm [F] 12x148mm [R] |
| **SPAKEN** | Stainless steel |
| **BANDEN** | Maxxis Rekon, 29x2.4", wire bead, EXO, 60TPI |
| **EXTRA'S** | KSA40 direct mount |
| **ACCESSORES** | |
| **VERLICHTING** | Giant Recon E HL50 Axa BlueLine Steady E6 rear |
| **SLOT** | Giant Rack-It MIK |
| **DRAGER** | MIK rack, system bag & basket compatibility |
| **SPATBORD/ KETTINGKAST** | Co-molded, 32-38t, adjustable |
| **LIMITS** | |
| **COMBINED MAXIMUM LOAD LIMIT** | 150kg |

**Adviesprijs: € 2.749,00**

## GEOMETRIE

| FRAME | S | M | L | XL |
|---|---|---|---|---|
| Zitbuis Lengte (mm) | 385 | 435 | 485 | 535 |
| Seat Post Insertion Depth (mm) | 200 | 240 | 260 | 260 |
| Zitbuis Hoek | 74,0° | 74,0° | 74,0° | 74,0° |
| Frame Lengte (horizontaal) (mm) | 580 | 600 | 620 | 640 |
| Balhoofdbuis Lengte (mm) | 100 | 115 | 130 | 145 |
| Balhoofdbuis Hoek | 68,0° | 68,0° | 68,0° | 68,0° |
| Vork Sprong (mm) | 46 | 46 | 46 | 46 |
| Naloop (mm) | 103,9 | 103,9 | 103,9 | 103,9 |
| Wielbasis (mm) | 1143 | 1165 | 1186 | 1208 |
| Liggende achtervork lengte (mm) | 470 | 470 | 470 | 470 |
| Bottom Bracket Drop (mm) | 60 | 60 | 60 | 60 |
| Stack (mm) | 613 | 627 | 641 | 655 |
| Reach (mm) | 404 | 420 | 436 | 452 |
| Stand Over Height (mm) | 723 | 753 | 788 | 808 |
| Stuur breedte (mm) | 750 | 750 | 780 | 780 |
| Stuurpen Lengte (mm) | 40 | 40 | 50 | 50 |
| Wielmaat | 29" | 29" | 29" | 29" |

*Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.*