

TALON E+ 2 EX



ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport 3, 85Nm, PedalPlus 6-Sensor technology
OVLÁDAČ	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
OVLÁDACIA JEDNOTKA	Giant RideControl Dash 2, full color LCD display
BATÉRIA	Giant EnergyPak 430Wh, Giant EnergyPak Plus 200Wh range extender compatible
NABÍJAČKA	Giant EnergyPak 4A smart charger
RÁM	
VEĽKOSTI	S, M, L, XL
RÁM	ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, integrated KSA40 kickstand mount
VIDLICA	SR Suntour XCM32, 100mm travel, 15x110mm thru-axle
KOMPONENTY	
RIADIDLÁ	Giant Connect TR riser 31.8x750mm [S/M], 31.8x780mm [L-XL]
GRIPY	Giant Sole-O
PREDSTAVEC	Giant Contact
SEDOVKA	Forged Aluminium, 30.9mm, 2-bolt micro adjustable
SEDADLO	Giant Ergo Trail ESG
PEDÁLE	platform
POHON	
RADENIE	Shimano CUES, LinkGlide
PREHADZOVAČKA	Shimano CUES, LinkGlide, 10-speed, Shadow+
BRZDY	Shimano MT-200, hydraulic disc, 180mm [F/R] rotors
BRZDOVÉ PÁKY	Shimano MT-200
KAZETA	Shimano CUES, LinkGlide, 10-speed, 11x48
REŤAZ	Shimano LinkGlide
KLUKY	Forged aluminium, [XS/S] 165mm, [M/L] 170mm, Direct-mount steel, 36t

KOLESÁ	
RÁFIKY	Giant GX03V, alloy
NÁBOJE	Shimano TC500, Boost, Center-Lock, 15x110mm [F] 12x148mm [R]
ŠPICE	Stainless steel
PNEUMATIKY	Maxxis Rekon, 29x2.4", wire bead, EXO, 60TPI
DOPLNKY	KSA40 direct mount
PRÍSLUŠENSTVO	
OSVETLENIE	Giant Recon E HL50 Axa BlueLine Steady E6 rear
ZAMKNÚŤ	Giant Rack-It MIK
NOSIČ	MIK rack, system bag & basket compatibility
BLATNÍK / CHRÁNIČ REŤAZE	Co-molded, 32-38t, adjustable
LIMITY	
COMBINED MAXIMUM LOAD LIMIT	150kg

Cena: 2 999 €

GEOMETRIA

RÁM	S	M	L	XL
Dĺžka sedlovej trubky (mm)	385	435	485	535
Hĺbka vloženia sedlovky (mm)	200	240	260	260
Uhol sedlovej trubky	74,0°	74,0°	74,0°	74,0°
Dĺžka hornej rámovej trubky (mm)	580	600	620	640
Dĺžka hlavovej trubky (mm)	100	115	130	145
Uhol hlavovej trubky	68,0°	68,0°	68,0°	68,0°
Offset vidlice (mm)	46	46	46	46
Trail (mm)	103,9	103,9	103,9	103,9
Rázvor (mm)	1143	1165	1186	1208
Dĺžka zadnej stavby (mm)	470	470	470	470
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	60	60	60	60
Stack - výška riadenia (mm)	613	627	641	655
Reach (mm)	404	420	436	452
Výška rámu od zeme (mm)	723	753	788	808
Šírka riaditok (mm)	750	750	780	780
Dĺžka predstavca (mm)	40	40	50	50
Rozmer kolies	29"	29"	29"	29"

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.