

TALON E+ 2 EX



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport 3, 85Nm, PedalPlus 6-Sensor technology
TIPALO	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
PRIKAZOVALNIK	Giant RideControl Dash 2, full color LCD display
BATERIJA	Giant EnergyPak 430Wh, Giant EnergyPak Plus 200Wh range extender compatible
CHARGER	Giant EnergyPak 4A smart charger
OKVIR	
VELIKOSTI	S, M, L, XL
OKVIR	ALUXX aluminum, Overdrive 1½ - 1⅞" head tube, integrated KSA40 kickstand mount
VILICE	SR Suntour XCM32, 100mm travel, 15x110mm thru-axle
KOMPONENTE	
KRMILO	Giant Connect TR riser 31.8x750mm [S/M], 31.8x780mm [L-XL]
GRIPS	Giant Sole-O
OPORA KRMILA	Giant Contact
OPORA SEDEŽA	Forged Aluminium, 30.9mm, 2-bolt micro adjustable
SEDEŽ	Giant Ergo Trail ESG
PEDALA	platform
POGON	
PRESTAVNE ROČICE	Shimano CUES, LinkGlide
ZADNJI MENJALNIK	Shimano CUES, LinkGlide, 10-speed, Shadow+
ZAVORE	Shimano MT-200, hydraulic disc, 180mm [F/R] rotors
ZAVORNE ROČICE	Shimano MT-200
VERIŽNIK	Shimano CUES, LinkGlide, 10-speed, 11x48
VERIGA	Shimano LinkGlide
GONILKE Z VERIŽNIKI	Forged aluminium, [XS/S] 165mm, [M/L] 170mm, Direct-mount steel, 36t

OBROČNIKI	
OBROČI	Giant GX03V, alloy
PESTA	Shimano TC500, Boost, Center-Lock, 15x110mm [F] 12x148mm [R]
NAPERE	Stainless steel
PLAŠČI	Maxxis Rekon, 29x2.4", wire bead, EXO, 60TPI
DODATKI	KSA40 direct mount
DODATNA OPREMA	
SVETILA	Giant Recon E HL50 Axa BlueLine Steady E6 rear
KLJUČAVNICA	Giant Rack-It MIK
PRTLJAŽNIK	MIK rack, system bag & basket compatibility
BLATNIKI/ŠČITNIK VERIGE	Co-molded, 32-38t, adjustable
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	150kg

GEOMETRIJA

OKVIR	S	M	L	XL
Dolžina sedežne cevi (mm)	385	435	485	535
Seat Post Insertion Depth (mm)	200	240	260	260
Kot sedežne cevi	74,0°	74,0°	74,0°	74,0°
Top Tube Length (mm)	580	600	620	640
Višina glave okvirja (mm)	100	115	130	145
Krmilni kot	68,0°	68,0°	68,0°	68,0°
Zamik vpetja osi (mm)	46	46	46	46
Trail (mm)	103,9	103,9	103,9	103,9
Medosna razdalja (mm)	1143	1165	1186	1208
Dolžina cevi ob verigi (mm)	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	613	627	641	655
Doseg (mm)	404	420	436	452
Višina zgornje cevi (mm)	723	753	788	808
Širina krmila (mm)	750	750	780	780
Dolžina opore krmila (mm)	40	40	50	50
Velikost obročnikov	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.