

# TALON E+ EX

**GIANT**



## SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	Giant SyncDrive Sport 2, 75Nm PedalPlus 6-sensor technology
<b>STEUEREINHEIT</b>	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
<b>DISPLAY</b>	Giant RideControl Dash 2, high-angle visibility, full color LCD display
<b>AKKU</b>	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
<b>CHARGER</b>	Giant EnergyPak smart charger 4A
<b>CONNECTIVITY</b>	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile

RAHMEN	
<b>GRÖSSEN</b>	S, M, L, XL
<b>FARBE</b>	Metallic Navy
<b>RAHMEN</b>	ALUXX aluminum, Overdrive 1½ - 1¼" head tube, integrated KSA40 kickstand mount
<b>GABEL</b>	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
<b>DÄMPFER</b>	n/a

KOMponenten	
<b>LENKER</b>	Giant Connect TR Riser 31.8x690~750mm
<b>GRIFFE</b>	Giant Sole-O Grip
<b>VORBAU</b>	Giant Contact
<b>SATTELSTÜTZE</b>	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
<b>SATTEL</b>	Giant Ergo Trail ESG
<b>PEDALE</b>	Anti-slip Platform

ANTRIEB	
<b>SCHALTHEBEL</b>	Shimano Cues
<b>SCHALTWERK</b>	Shimano Cues 9-speed
<b>BREMSSEN</b>	Shimano MT200, hydraulic disc, 180mm [F/R]
<b>BREMSHEBEL</b>	Shimano MT-200
<b>KASSETTE</b>	Shimano Cues, 11-41T, 9-speed
<b>KETTE</b>	KMC eGlide NP/BK, e-bike optimized
<b>KURBEL</b>	Forged allumin direct-mount chainring steel 36T, Forged aluminium crank arms
<b>TRETLAGER</b>	n/a

LAUFRÄDER	
<b>FELGEN</b>	Giant GX03V alluminum
<b>NABE</b>	eTracker Boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
<b>SPEICHEN</b>	Stainless steel
<b>REIFEN</b>	Maxxis Rekon 29x2.4"
ACCESSORIES	
<b>BELEUCHTUNG</b>	Giant Recon E HL50 Axa BlueLine Steady E6 rear
<b>GEPÄCKTRÄGER</b>	Giant Rack-It MIK

## GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	385	435	485	535
Seat Post Insertion Depth (mm)	200	240	260	260
Sitzrohrwinkel	78.0°	74.0°	74.0°	74.0°
Oberrohrlänge (mm)	580	600	620	640
Steuerrohr-Länge (mm)	100	115	130	145
Steuerrohr-Winkel	68.0°	68.0°	68.0°	68.0°
Gabelneigung (mm)	46	46	46	46
Radstand (mm)	1144	1165	1187	1209
Kettenstreben-Länge (mm)	470	470	470	470
Tretlager-Höhe (mm)	60	60	60	60
Stack (mm)	613	627	641	655
Reach (mm)	404	420	436	452
Überstandshöhe (mm)	723	753	788	808
Lenkerbreite (mm)	750	750	780	780
Vorbaulänge (mm)	50	50	50	50
Radgröße	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.