

TALON E+ EX

GIANT



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Sport ² , 75Nm PedalPlus 6-sensor technology
COMMANDE	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
ECRAN	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATTERIE	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604)
ENERGYPAK PLUS COMPATIBLES	CO2 Neutral production Giant EnergyPak Plus 200 range extender compatible
CHARGEUR	Giant EnergyPak smart charger 4A
CONNECTIVITÉ	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile, E-Lock, FindMyBike
CADRE	
TAILLES	S, M, L, XL
COLORIS	Metallic Navy
CADRE	ALUXX aluminum, Overdrive 1½ - 1¼" head tube, integrated KSA40 kickstand mount
FOURCHE	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
AMORTISSEUR	n/a
COMPOSANTS	
CINTRE	Giant Connect TR Riser 31.8x690-750mm
POIGNÉES	Giant Sole-O Grip
POTENCE	Giant Contact
TIGE DE SELLE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELLE	Giant Ergo Trail ESG
PÉDALES	Anti-slip Platform
DÉRAILLEUR	
MANETTES	Shimano Cues
DÉRAILLEUR ARRIÈRE	Shimano Cues 9-speed
FREINS	Shimano MT200, hydraulic disc, 180mm [F/R]
LEVIERS DE FREIN	Shimano MT-200
CASSETTE	Shimano Cues, 11-41T, 9-speed
CHAÎNE	KMC eGlide NP/BK, e-bike optimized
PÉDALIER	Forged allumin direct-mount chainring steel 36T, Forged aluminium crank arms
BOITIER DE PÉDALIER	n/a

ROUES	
JANTES	Giant GX03V alluminium
MOYEURS	eTracker Boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
RAYONS	Stainless steel
PNEUS	Maxxis Rekon 29x2.4"
LIMITES	
COMPATIBILITÉ	Tire Checker Aegis
ACCESSOIRES	
ECLAIRAGE	Giant Recon E HL50 Axa BlueLine Steady E6 rear
PORTE-BAGAGES	Giant Rack-It MIK

Prix Public Conseillé: 2 800,00 €

GÉOMÉTRIE

CADRE	S	M	L	XL
Longueur de tube de selle (mm)	385	435	485	535
Seat Post Insertion Depth (mm)	200	240	260	260
Angle de tube de selle	78,0°	74,0°	74,0°	74,0°
Longueur du tube supérieur (mm)	580	600	620	640
Longueur du tube de direction (mm)	100	115	130	145
Angle du tube de direction	68,0°	68,0°	68,0°	68,0°
Déport de fourche (mm)	46	46	46	46
Empattement (mm)	1144	1165	1187	1209
Longueur des bases (mm)	470	470	470	470
Drop du boîtier de pédalier (mm)	60	60	60	60
Stack (mm)	613	627	641	655
Reach (mm)	404	420	436	452
Hauteur en statique (mm)	723	753	788	808
Largeur de cintre (mm)	750	750	780	780
Longueur de potence (mm)	50	50	50	50
Diamètre des roues	29"	29"	29"	29"

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.