



## SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport 2, 75Nm PedalPlus 6-sensor technology
SENSOR	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
PRIKAZ	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATERIJA	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
OKVIR	
VELIČINE	S, M, L, XL
BOJE	Metallic Navy
OKVIR	ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, integrated KSA40 kickstand mount
VILICA	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
AMORTIZER	n/a
KOMPONENTE	
VOLAN	Giant Connect TR Riser 31.8x690-750mm
GRIPS	Giant Sole-O Grip
LULA VOLANA	Giant Contact
CIJEV SJEDALA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SJEDALO	Giant Ergo Trail ESG
PEDALE	Anti-slip Platform
POGON	
RUČICE MJENJAČA	Shimano Cues
STRAŽNJI MJENJAČ	Shimano Cues 9-speed
KOČNICE	Shimano MT200, hydraulic disc, 180mm [F/R]
RUČICE KOČNICA	Shimano MT-200
KAZETA	Shimano Cues, 11-41T, 9-speed
LANAC	KMC eGlide NP/BK, e-bike optimized
POGON	Forged allumin direct-mount chainring steel 36T, Forged aluminium crank arms
OSOVINA POGONA (BB)	n/a

KOTAČI	
OBRUČI	Giant GX03V alluminium
NABE	eTracker Boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
ŽBICE	Stainless steel
GUME	Maxxis Rekon 29x2.4"
DODACI	
SVJETLA	Giant Recon E HL50 Axa BlueLine Steady E6 rear
NOSAČ	Giant Rack-It MIK

## GEOMETRIJA

OKVIR	S	M	L	XL
Dužina cijevi sjedala (mm)	385	435	485	535
Seat Post Insertion Depth (mm)	200	240	260	260
Kut cijevi sjedala	78,0°	74,0°	74,0°	74,0°
Dužina gornje cijevi (mm)	580	600	620	640
Dužina prednje cijevi (mm)	100	115	130	145
Kut vilice	68,0°	68,0°	68,0°	68,0°
Zakrivljenost vilice (offset) (mm)	46	46	46	46
Međuosovinski razmak kotača (mm)	1144	1165	1187	1209
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	470	470	470	470
Položaj osovine pogona (mm)	60	60	60	60
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	613	627	641	655
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	404	420	436	452
Prekoračna visina (mm)	723	753	788	808
Širina volana (mm)	750	750	780	780
Dužina lule volana (mm)	50	50	50	50
Veličina kotača	29"	29"	29"	29"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.