

TALON E+



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport 2, 75Nm PedalPlus 6-sensor technology
BEDIENINGSUNIT	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, high-angle visibility, full color LCD display
ACCU	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LADER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	S, M, L, XL
KLEUREN	Asphalt Green
FRAME	ALUXX aluminum, Overdrive 1½ - 1¾" head tube, integrated KSA40 kickstand mount
VOORVORK	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
DEMPER	n/a
ONDERDELEN	
STUUR	Giant Connect TR Riser 31.8x690~750mm
HANDVATTEN	Giant Sole-O Grip
STUURPEN	Giant Contact
ZADELPEN	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
ZADEL	Giant Ergo Trail ESG
PEDALEN	Anti-slip Platform
AFMONTAGE	
SHIFTERS	Shimano Cues
ACHTERDERAILLEUR	Shimano Cues 9-speed
REMMEN	Shimano MT200, hydraulic disc, 180mm [F/R]
REMHENDELS	Shimano MT-200
CASSETTE	Shimano Cues, 11-41T, 9-speed
AANDRIJVING	KMC eGlide NP/BK, e-bike optimized
CRANKSET	Forged allumin direct-mount chainring steel 36T, Forged alumium crank arms
BOTTOM BRACKET	n/a

WIELSET	
VELGEN	Giant GX03V alluminum
NAVEN	eTracker Boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
SPAKEN	Stainless steel
BANDEN	Maxxis Rekon 29x2.4"
ACCESSOIRES	
VERLICHTING	-
DRAGER	-

Adviesprijs: € 2.799,00

GEOMETRIE

FRAME	S	M	L	XL
Zitbuis Lengte (mm)	385	435	485	535
Seat Post Insertion Depth (mm)	200	240	260	260
Zitbuis Hoek	74,0°	74,0°	74,0°	74,0°
Frame Lengte (horizontaal) (mm)	580	600	620	640
Balhoofdbuis Lengte (mm)	100	115	130	145
Balhoofdbuis Hoek	68,0°	68,0°	68,0°	68,0°
Vork Sprong (mm)	46	46	46	46
Naloop (mm)	103,9	103,9	103,9	103,9
Wielbasis (mm)	1143	1165	1186	1208
Liggende achtervork lengte (mm)	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	613	627	641	655
Reach (mm)	404	420	436	452
Stand Over Height (mm)	723	753	788	808
Stuur breedte (mm)	750	750	780	780
Stuurpen Lengte (mm)	40	40	50	50
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.