

TALON E+



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport 2, 75Nm PedalPlus 6-sensor technology
TIPALO	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
PRIKAZOVALNIK	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATERIJA	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Asphalt Green, Electric Blue, Meteor Storm
OKVIR	ALUXX aluminum, Overdrive 1½ - 1¼" head tube, integrated KSA40 kickstand mount
VILICE	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
AMORTIZER	n/a
KOMPONENTE	
KRMILO	Giant Connect TR Riser 31.8x690~750mm
GRIPS	Giant Sole-O Grip
OPORA KRMILA	Giant Contact
OPORA SEDEŽA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SEDEŽ	Giant Ergo Trail ESG
PEDALA	Anti-slip Platform
POGON	
PRESTAVNE ROČICE	Shimano Cues
ZADNJI MENJALNIK	Shimano Cues 9-speed
ZAVORE	Shimano MT200, hydraulic disc, 180mm [F/R]
ZAVORNE ROČICE	Shimano MT-200
VERIŽNIK	Shimano Cues, 11-41T, 9-speed
VERIGA	KMC eGlide NP/BK, e-bike optimized
GONILKE Z VERIŽNIKI	Forged allumin direct-mount chainring steel 36T, Forged alumium crank arms
BOTTOM BRACKET	n/a

OBROČNIKI	
OBROČI	Giant GX03V alluminum
PESTA	eTracker Boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
NAPERE	Stainless steel
PLAŠČI	Maxxis Rekon 29x2.4"
DODATNA OPREMA	
SVETILA	-
PRTLJAŽNIK	-

GEOMETRIJA

OKVIR	S	M	L	XL
Dolžina sedežne cevi (mm)	385	435	485	535
Seat Post Insertion Depth (mm)	200	240	260	260
Kot sedežne cevi	74,0°	74,0°	74,0°	74,0°
Top Tube Length (mm)	580	600	620	640
Višina glave okvirja (mm)	100	115	130	145
Krmilni kot	68,0°	68,0°	68,0°	68,0°
Zamik vpetja osi (mm)	46	46	46	46
Trail (mm)	103,9	103,9	103,9	103,9
Medosna razdalja (mm)	1143	1165	1186	1208
Dolžina cevi ob verigi (mm)	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	613	627	641	655
Doseg (mm)	404	420	436	452
Višina zgornje cevi (mm)	723	753	788	808
Širina krmila (mm)	750	750	780	780
Dolžina opore krmila (mm)	40	40	50	50
Velikost obročnikov	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.