

# TCR ADVANCED 0 AXS

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLORS</b>	Frost Silver
<b>FRAME</b>	Advanced-Grade Composite, 12x142mm thru-axle, disc
<b>FORK</b>	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
<b>GRIPS</b>	Stratus Lite 3.0
<b>STEM</b>	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
<b>SEATPOST</b>	Giant Variant, composite, -5/+15mm offset
<b>SADDLE</b>	Giant Approach
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM eTap Rival AXS
<b>FRONT DERAILLEUR</b>	SRAM eTap Rival AXS
<b>REAR DERAILLEUR</b>	SRAM eTap Rival AXS
<b>BRAKES</b>	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	SRAM Rival AXS
<b>CASSETTE</b>	SRAM Rival, 12-speed, 10x36
<b>CHAIN</b>	SRAM Rival D1
<b>CRANKSET</b>	SRAM Rival, 33/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant SLR 2 36 WheelSystem, [F]36mm, [R]36mm
<b>HUBS</b>	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t pawl driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim Sprint
<b>TIRES</b>	Giant Gavia Course 1, tubeless, 700x25c (28mm), folding
<b>EXTRAS</b>	tubeless prepared, 33mm max tire size
LIMITS	
<b>MAX TIRE CLEARANCE</b>	33mm

## GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,5°	73,0°	73,0°	72,5°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72	64	59	59	59	59
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69,5	69,5	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	703	722	743	771	798	822
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.