



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S, M, M/L, L, XL
ЦВЯТ	Frost Silver
РАМКА	Advanced-Grade Composite, 12x142mm thru-axle, disc
ВИЛКА	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
ГРИПОВЕ	Stratus Lite 2.0
ЛАПА	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
КОЛЧЕ ЗА СЕДАЛКА	Giant Variant, composite, -5/+15mm offset
СЕДАЛКА	Giant Approach
ПЕДАЛИ	N/A
DRIVETRAIN	
КОМАНДИ	Shimano 105 Di2
ПРЕДЕН ДЕРАЙЛЪОР	Shimano 105 Di2 FD-R8150
ЗАДЕН ДЕРАЙЛЪОР	Shimano 105 Di2 RD-R8150
СПИРАЧКИ	Shimano 105 Di2 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]140mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano 105 Di2
КАСЕТА	Shimano 105, 12-speed, 11x34
ВЕРИГА	KMC X12L-1
КУРБЕЛ	Shimano 105, 36/52 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
СРЕДНА КАСЕТА	Shimano, press fit

КАПЛИ	
ШИНИ	Giant SLR 2 36 WheelSystem, [F]36mm, [R]36mm
ГЛАВИНИ	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t pawl driver, CenterLock, 12mm thru-axle
СПИЦИ	Sapim Sprint
ГУМИ	Giant Gavia Course 1, tubeless, 700x25c (28mm), folding
ЕКСТРИ	tubeless prepared, 33mm max tire size
ЛИМИТИ	
MAX TIRE CLEARANCE	33mm

ГЕОМЕТРИЯ

РАМКА	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,5°	73,0°	73,0°	72,5°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72	64	59	59	59	59
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69,5	69,5	67	67	67
Stack (mm)	517	528	545	562	581	596
Обсер (mm)	376	383	388	393	402	412
Stand Over Height (mm)	703	722	743	771	798	822
Ширина на Кормило (mm)	400	400	420	420	440	440
Дължина на Лапа (mm)	80	90	100	110	110	120
Дължина на Курбел (mm)	170	170	172,5	172,5	175	175
Размер на Каплите	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.