

TCR ADVANCED 0-PC



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Teal
CUADRO	Advanced-Grade Composite, 12x142mm thru-axle, disc
HORQUILLA	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPONENTES	
MANILLAR	Giant Contact XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
PUÑOS	Stratus Lite 2.0
POTENCIA	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
TIJA DE SILLÍN	Giant Variant, composite, -5/+15mm offset
SILLÍN	Giant Approach
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano 105 Di2
DESVIADOR	Shimano 105 Di2 FD-R8150
CAMBIO TRASERO	Shimano 105 Di2 RD-R8150
FRENOS	Shimano 105 Di2 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	Shimano 105 Di2
CASETTE	Shimano 105, 12-speed, 11x34
CADENA	KMC X12L-1
JGO. PLATOS Y BIELAS	Shimano 105, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
CAJA DE PEDALIER	Shimano, press fit

RUEDAS	
LLANTAS	Giant SLR 2 40 WheelSystem, [F]40mm, [R]40mm
BUJES	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t pawl driver, CenterLock, 12mm thru-axle
RADIOS	Sapim
CUBIERTAS	Giant Gavia Course 0, tubeless, 700x30c, folding
EXTRAS	tubeless prepared
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	33mm

Precio: 3.899,00 €

GEOMETRÍA

CUADRO	XS	S	M	ML	L	XL
Longitud del tubo del sillín (mm)	425	445	470	500	530	560
Ángulo del tubo del sillín	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Longitud del tubo superior (mm) (mm)	520	535	550	565	580	600
Longitud del tubo de dirección (mm) (mm)	120	130	145	165	185	200
Ángulo del tubo de dirección	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Inclinación de la horquilla (mm)	45	45	45	45	45	45
Trail (mm) (mm)	72,1	64	59,2	59,2	59,2	59,2
Distancia entre ejes (mm) (mm)	976	977	980	991	1006	1020
Longitud de la vaina (mm) (mm)	405	405	405	405	405	405
Caída del eje de pedalier (mm) (mm)	72	70	70	67	67	67
Stack (mm) (mm)	517	528	545	562	581	596
Reach (mm) (mm)	376	383	388	393	402	412
Altura del suelo al tubo (mm) (mm)	719	734	752	768	786	803
Ancho del manillar (mm) (mm)	380	380	400	400	420	420
Longitud de la potencia (mm) (mm)	80	90	100	110	110	120
Longitud de las bielas (mm) (mm)	165	165	170	170	172,5	172,5

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.