

TCR ADVANCED 0 PC



SPECS

QUADRO	
TAMANHOS	XS, S, M, M/L, L, XL
CORES	Frost Silver
QUADRO	Advanced-Grade Composite, 12x142mm thru-axle, disc
FORQUILHA	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPONENTES	
GUIADOR	Giant Contact XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
PUNHOS	Stratus Lite 2.0
AVANÇO	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
ESPIGÃO DE SELIM	Giant Variant, composite, -5/+15mm offset
SELIM	Giant Approach
PEDAIS	N/A
TRANSMISSÃO	
MANETES	Shimano 105 Di2
DESVIADOR DIANTEIRO	Shimano 105 Di2 FD-R8150
DESVIADOR TRASEIRO	Shimano 105 Di2 RD-R8150
TRAVÕES	Shimano 105 Di2 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]140mm
MANÍPULOS DOS TRAVÕES	Shimano 105 Di2
CASSETTE	Shimano 105, 12-speed, 11x34
CORRENTE	KMC X12L-1
CONJUNTO PEDALEIRO	Shimano 105, 36/52 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
MOVIMENTO CENTRAL	Shimano, press fit

RODAS	
AROS	Giant SLR 2 36 WheelSystem, [F]36mm, [R]36mm
CUBOS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t pawl driver, CenterLock, 12mm thru-axle
RAIOS	Sapim Sprint
PNEUS	Giant Gavia Course 1, tubeless, 700x25c (28mm), folding
EXTRAS	tubeless prepared, 33mm max tire size
LIMITES	
FOLGA MÁXIMA DO PNEU	33mm

Preço: 3 499,00 €

GEOMETRIA

QUADRO	XS	S	M	ML	L	XL
Comprimento do tubo do assento (mm)	425	445	470	500	530	560
Ângulo do tubo do assento	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Comprimento do tubo superior (mm)	520	535	550	565	580	600
Comprimento do tubo principal (mm)	120	130	145	165	185	200
Ângulo do tubo principal	71,0°	72,3°	73,5°	73,0°	73,0°	72,5°
Garfo ancinho (mm)	45	45	45	45	45	45
Trilha (mm)	72	64	59	59	59	59
distância entre eixos (mm)	976	977	980	991	1006	1020
Comprimento Chain Stay (mm)	405	405	405	405	405	405
Suporte inferior (mm)	72	69,5	69,5	67	67	67
Pilha (mm)	517	528	545	562	581	596
Alcançar (mm)	376	383	388	393	402	412
Altura do standover (mm)	703	722	743	771	798	822
Largura do guidão (mm)	400	400	420	420	440	440
Comprimento da haste (mm)	80	90	100	110	110	120
Comprimento da Manivela (mm)	170	170	172,5	172,5	175	175
Tamanho da roda	700C	700C	700C	700C	700C	700C

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.