



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Frost Silver
OKVIR	Advanced-Grade Composite, 12x142mm thru-axle, disc
VILICE	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 2.0
OPORA KRMILA	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
OPORA SEDEŽA	Giant Variant, composite, -5/+15mm offset
SEDEŽ	Giant Approach
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	Shimano 105 Di2
PREDNJI MENJALNIK	Shimano 105 Di2 FD-R8150
ZADNJI MENJALNIK	Shimano 105 Di2 RD-R8150
ZAVORE	Shimano 105 Di2 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]140mm
ZAVORNE ROČICE	Shimano 105 Di2
VERIŽNIK	Shimano 105, 12-speed, 11x34
VERIGA	KMC X12L-1
GONILKE Z VERIŽNIKI	Shimano 105, 36/52 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant SLR 2 36 WheelSystem, [F]36mm, [R]36mm
PESTA	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t pawl driver, CenterLock, 12mm thru-axle
NAPERE	Sapim Sprint
PLAŠČI	Giant Gavia Course 1, tubeless, 700x25c (28mm), folding
DODATKI	tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	425	445	470	500	530	560
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	120	130	145	165	185	200
Krmilni kot	71,0°	72,3°	73,5°	73,0°	73,0°	72,5°
Zamik vpetja osi (mm)	45	45	45	45	45	45
Trail (mm)	72	64	59	59	59	59
Medosna razdalja (mm)	976	977	980	991	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69,5	69,5	67	67	67
Oddaljenost zgornje cevi od gonilne osi (mm)	517	528	545	562	581	596
Doseg (mm)	376	383	388	393	402	412
Višina zgornje cevi (mm)	703	722	743	771	798	822
Širina krmila (mm)	400	400	420	420	440	440
Dolžina opore krmila (mm)	80	90	100	110	110	120
Dolžina gonilke (mm)	170	170	172,5	172,5	175	175
Velikost obročnikov	700C	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.