

TCR ADVANCED 0 PC



SPECS

RAM	
STORLEKAR	XS, S, M, M/L, L, XL
FÄRGER	Frost Silver
RAM	Advanced-Grade Composite, 12x142mm thru-axle, disc
GAFFEL	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GREPPAR	Stratus Lite 2.0
STAM	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SADELSTOLPE	Giant Variant, composite, -5/+15mm offset
SADEL	Giant Approach
PEDALER	N/A
DRIVLINA	
VÄXLAR	Shimano 105 Di2
FRAMVÄXEL	Shimano 105 Di2 FD-R8150
BAKVÄXEL	Shimano 105 Di2 RD-R8150
BROMSAR	Shimano 105 Di2 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]140mm
BROMSSPAKAR	Shimano 105 Di2
KASSETT	Shimano 105, 12-speed, 11x34
KEDJA	KMC X12L-1
VEVPARTI	Shimano 105, 36/52 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BROMSREGLAGE	Shimano, press fit

HJUL	
FÄLGAR	Giant SLR 2 36 WheelSystem, [F]36mm, [R]36mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t pawl driver, CenterLock, 12mm thru-axle
EKRAR	Sapim Sprint
DÄCK	Giant Gavia Course 1, tubeless, 700x25c (28mm), folding
EXTRAFUNKTIONER	tubeless prepared, 33mm max tire size
GRÄNSER	
MAX DÄCKAVSTÅND	33mm

Price: 47 090,00 kr

GEOMETRY

RAM	S	M	ML	L	XL
Längd sadelrör (mm)	445	470	500	530	560
Vinkel sadelrör	74,0°	73,5°	73,0°	73,0°	72,5°
Topprörets längd (mm)	535	550	565	580	600
Styrhuvud Längd (mm)	130	145	165	185	200
Vinkel styrhuvud	72,3°	73,5°	73,0°	73,0°	72,5°
Gaffelvinkel (mm)	45	45	45	45	45
Spår (mm)	64	59	59	59	59
Hjulbas (mm)	977	980	991	1006	1020
Kedjestagslängd (mm)	405	405	405	405	405
Nedre fäste Drop (mm)	69,5	69,5	67	67	67
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Stå över höjden (mm)	722	743	771	798	822
Styrets bredd (mm)	400	420	420	440	440
Stamlängd (mm)	90	100	110	110	120
Vevlängd (mm)	170	172,5	172,5	175	175
Hjulstorlek	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.