

TCR ADVANCED 0 (PRO COMPACT)

GIANT



SPECS

| FRAME | |
|------------------|--|
| SIZES | S, M, M/L, L |
| COLORS | Alpine Green |
| FRAME | Advanced-Grade Composite, 12x142mm thru-axle, disc |
| FORK | Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc |
| COMPONENTS | |
| HANDLEBAR | Giant Contact S:38cm, M:40cm, M/L:40cm, L:42cm |
| GRIPS | Stratus Lite 2.0 |
| STEM | Giant Contact AeroLight S:90mm, M:100mm, M/L:110mm, L:110mm |
| SEATPOST | Giant Variant, composite, -5/+15mm offset |
| SADDLE | Giant Approach |
| DRIVETRAIN | |
| SHIFTERS | Shimano 105 Di2 ST-R7170 |
| FRONT DERAILLEUR | Shimano 105 Di2 FD-R7150 |
| REAR DERAILLEUR | Shimano 105 Di2 RD-R7150 |
| BRAKES | Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]140mm |
| BRAKE LEVERS | Shimano 105 Di2 |
| CASSETTE | Shimano 105, 12-speed, 11x34 |
| CHAIN | KMC X12L-1 |
| CRANKSET | Shimano 105, 36/52 S:165mm, M:170mm, M/L:170mm, L:172.5mm |
| BOTTOM BRACKET | Shimano, press fit |

| WHEELS | |
|--------------------|--|
| RIMS | Giant SLR 2 40 WheelSystem, [F]40mm, [R]40mm |
| HUBS | [F] Giant Alloy, CenterLock, 12mm thru-axle [R] Giant Alloy, 3 pawl 30t driver, CenterLock, 12mm thru-axle |
| SPOKES | Sapim Sprint |
| TIRES | Giant Gavia Course 0, tubeless, 700x28c (28mm), folding |
| EXTRAS | Tubeless prepared, 33mm max tyre size |
| LIMITS | |
| MAX TIRE CLEARANCE | 33mm |

Price: \$6,499.00

GEOMETRY

| FRAME | XS | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 425 | 445 | 470 | 500 | 530 | 560 |
| Seat Tube Angle | 74.5° | 74.0° | 73.5° | 73.0° | 73.0° | 72.5° |
| Top Tube Length (mm) | 520 | 535 | 550 | 565 | 580 | 600 |
| Head Tube Length (mm) | 120 | 130 | 145 | 165 | 185 | 200 |
| Head Tube Angle | 71.0° | 72.3° | 73.0° | 73.0° | 73.0° | 73.0° |
| Fork Rake (mm) | 45 | 45 | 45 | 45 | 45 | 45 |
| Trail (mm) | 72.1 | 64 | 59.2 | 59.2 | 59.2 | 59.2 |
| Wheelbase (mm) | 976 | 977 | 980 | 991 | 1006 | 1020 |
| Chain Stay Length (mm) | 405 | 405 | 405 | 405 | 405 | 405 |
| Bottom Bracket Drop (mm) | 72 | 70 | 70 | 67 | 67 | 67 |
| Stack (mm) | 517 | 528 | 545 | 562 | 581 | 596 |
| Reach (mm) | 376 | 383 | 388 | 393 | 402 | 412 |
| Stand Over Height (mm) | 719 | 734 | 752 | 768 | 786 | 803 |
| Stem Length (mm) | 80 | 90 | 100 | 110 | 110 | 120 |
| Crank Length (mm) | 165 | 165 | 170 | 170 | 172.5 | 172.5 |

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.