

TCR ADVANCED 0 (PRO COMPACT)

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Alpine Green
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORK	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
STEM	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Giant Variant, composite, -5/+15mm offset
SADDLE	Giant Approach
DRIVETRAIN	
SHIFTERS	Shimano 105 Di2
FRONT DERAILLEUR	Shimano 105 Di2 FD-R8150
REAR DERAILLEUR	Shimano 105 Di2 RD-R8150
BRAKES	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano 105 Di2
CASSETTE	Shimano 105, 12-speed, 11x34
CHAIN	KMC X12L-1
CRANKSET	Shimano 105, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 2 40 WheelSystem, [F]40mm, [R]40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T pawl driver, CenterLock, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Course 0, tubeless, 700x28c (28mm), folding
EXTRAS	tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

Suggested Retail Price (CDN): \$5,199.00

FRAME GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72.1	64	59.2	59.2	59.2	59.2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	719	734	752	768	786	803
Handlebar Width (mm)	380	380	400	400	420	420
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172.5	172.5

All prices and specifications are subject to change without notice.