



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Asphalt Green, Mars Dust
CADRE	Advanced-Grade Composite, 12x142mm thru-axle, disc
FOURCHE	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPOSANTS	
CINTRE	Giant Contact XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
POIGNÉES	Stratus Lite 2.0
POTENCE	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
TIGE DE SELLE	Giant Variant, composite, -5/+15mm offset
SELLE	Giant Approach
PÉDALES	N/A
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano 105 Di2
DÉRAILLEUR AVANT	Shimano 105 Di2 FD-R8150
DÉRAILLEUR ARRIÈRE	Shimano 105 Di2 RD-R8150
FREINS	Shimano 105 Di2 hydraulic, Giant MPH rotors [F]160mm, [R]140mm
LEVIER DE FREIN	Shimano 105 Di2
CASSETTE	Shimano 105, 12-speed, 11x36
CHAÎNE	KMC X12L-1
PÉDALIER	Shimano 105, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
PÉDALIER	Shimano, press fit

ROUES	
JANTES	Giant P-R2, [F]36mm, [R]36mm
MOYEUX	12mm thru-axle
RAYONS	stainless
PNEUS	Giant Gavia Course 1, tubeless, 700x25c (28mm), folding
EXTRAS	tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GÉOMÉTRIE

CADRE	XS	S	M	ML	L	XL
Longueur de tube de selle (mm)	425	445	470	500	530	560
Angle de tube de selle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Longueur du tube supérieur (mm)	520	535	550	565	580	600
Longueur du tube de direction (mm)	120	130	145	165	185	200
Angle du tube de direction	71,0°	72,3°	73,5°	73,0°	73,0°	72,5°
Déport de fourche (mm)	45	45	45	45	45	45
Chasse (mm)	72	64	59	59	59	59
Empattement (mm)	976	977	980	991	1006	1020
Longueur des bases (mm)	405	405	405	405	405	405
Hauteur du boîtier de pédalier (mm)	72	69,5	69,5	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Hauteur d'enjambement (mm)	703	722	743	771	798	822
Largeur de cintre (mm)	400	400	420	420	440	440
Longueur de potence (mm)	80	90	100	110	110	120
Longueur des manivelles (mm)	170	170	172,5	172,5	175	175
Diamètre des roues	700C	700C	700C	700C	700C	700C

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.